

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name : K025-K60 COLOREX 2717

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Paint stripper  
stance/Mixture

### 1.3 Details of the supplier of the safety data sheet

Company : hebro chemie- ZN der Rockwood Specialties Group  
GmbH  
Rostocker Str. 40  
41199 Mönchengladbach

Contact person : Zentrale hebro chemie  
Telephone : +49 (0) 2166 6009-0  
Telefax : +49 (0) 2166 6009-99

Contact person product safety : Abteilung Produktsicherheit  
Telephone : +49(0)2166 6009-311  
E-mail address : msds.de@hebro-chemie.de

### 1.4 Emergency telephone number

: Giftinformationszentrum Erfurt:  
+49 (0) 361 730 730

---

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4 : H302: Harmful if swallowed.

Acute toxicity, Category 3 : H331: Toxic if inhaled.

Skin corrosion, Category 1A : H314: Causes severe skin burns and eye damage.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H302 Harmful if swallowed.

Version: 2.5

Revision Date: 31.03.2020

Print Date: 01.04.2020

H314 Causes severe skin burns and eye damage.  
H331 Toxic if inhaled.

Supplemental Hazard Statements : EUH071 Corrosive to the respiratory tract.

Precautionary statements : **Prevention:**  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Hazardous components which must be listed on the label:

Benzyl alcohol

Formic Acid

Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs.

**2.3 Other hazards**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

The information required is contained in this Material Safety Data Sheet.

**SECTION 3: Composition/information on ingredients**

**3.2 Mixtures**

Chemical nature : Preparation of organic acids, alcohol and tensides

**Hazardous components**

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (% w/w)
Benzyl alcohol	100-51-6 202-859-9 01-2119492630-38	Acute Tox. 4; H332 Acute Tox. 4; H302 Eye Irrit. 2; H319	>= 50 - < 65
Formic Acid	64-18-6	Flam. Liq. 3; H226	>= 25 - < 50

Version: 2.5

Revision Date: 31.03.2020

Print Date: 01.04.2020

	200-579-1 01-2119491174-37	Acute Tox. 4; H302 Acute Tox. 3; H331 Skin Corr. 1A; H314 Eye Dam. 1; H318	
Isotridecyl alcohol, ethoxylated (3-6 EO)	9043-30-5 500-027-2	Eye Dam. 1; H318 Aquatic Chronic 3; H412	>= 3 - < 5
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs.	85536-14-7 287-494-3 01-2119490234-40	Acute Tox. 4; H302 Skin Corr. 1C; H314 Aquatic Chronic 3; H412	>= 2.5 - < 5
1,3-Dibutyl-2-thiourea	109-46-6 203-674-6	Acute Tox. 4; H302	>= 1 - < 2.5

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : Provide fresh air.  
Keep patient warm and at rest.  
If symptoms persist, call a physician.
- In case of skin contact : Take off all contaminated clothing immediately.  
After contact with skin, wash immediately with plenty of soap and water.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Seek medical advice.
- If swallowed : Call a physician immediately.  
Keep at rest.  
Do NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Erythema

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.  
For specialist advice physicians should contact the Poisons Information Service.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry powder  
Water spray jet

Version: 2.5

Revision Date: 31.03.2020

Print Date: 01.04.2020

---

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Hazardous decomposition products formed under fire conditions.  
Carbon monoxide  
Nitrogen oxides (NOx)

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Use water spray to cool unopened containers.  
Suppress (knock down) gases/vapours/mists with a water spray jet.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Ensure adequate ventilation.  
Do not breathe vapours, aerosols.  
Remove all sources of ignition.

### 6.2 Environmental precautions

Environmental precautions : Do not empty into drains.  
Inform the relevant authorities if it enters sewers, aquatic environment or soil.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

See chapter  
8  
and  
13

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Keep away from open flames, hot surfaces and sources of ignition.

---

Version: 2.5

Revision Date: 31.03.2020

Print Date: 01.04.2020

Take precautionary measures against static discharges.  
 Avoid contact with skin and eyes.  
 Do not breathe vapours or spray mist.  
 When using do not eat, drink or smoke.  
 For personal protection see section 8.

Advice on protection against fire and explosion : Vapours are heavier than air and may spread along floors.  
 Vapours may form explosive mixtures with air.

## 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Follow the water regulations. Keep only in the original container in a cool, well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Further information on storage conditions : Keep only in the original container in a cool, well-ventilated place. Keep away from heat. Keep away from sources of ignition - No smoking. Keep at temperatures between - 7°C and 40°C.

Advice on common storage : Incompatible with oxidizing agents.

## 7.3 Specific end use(s)

Specific use(s) : Paint stripper

# SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Formic Acid	64-18-6	TWA	5 ppm 9 mg/m <sup>3</sup>	2006/15/EC
Further information	Indicative			
		TWA	5 ppm 9.6 mg/m <sup>3</sup>	GB EH40
Further information	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Benzyl alcohol	Workers	Inhalation	Long-term systemic effects	22 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	110 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	8 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	40 mg/kg bw/day
Formic Acid	Workers	Inhalation	Long-term local effects	9.5 mg/m <sup>3</sup>

**SAFETY DATA SHEET**  
 according to Regulation (EC) No. 1907/2006  
**K025-K60 COLOREX 2717**



Version: 2.5

Revision Date: 31.03.2020

Print Date: 01.04.2020

	Workers	Inhalation	Long-term systemic effects	9.5 mg/m <sup>3</sup>
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs.	Workers	Inhalation	Long-term local effects	12 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	12 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	170 mg/kg

**Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:**

Substance name	Environmental Compartment	Value
Benzyl alcohol		
Remarks:	No data available	
Formic Acid	Fresh water	2 mg/l
	Marine water	0.2 mg/l
	Sewage treatment plant	7.2 mg/l
	Fresh water sediment	13.4 mg/kg
	Marine sediment	1.34 mg/kg
	Soil	1.5 mg/kg
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs.	Fresh water	0.287 mg/l
	Marine water	0.0287 mg/l
	Sewage treatment plant	3.43 mg/l
	Intermittent use/release	0.0167 mg/l
	Fresh water sediment	0.287 mg/kg
	Marine sediment	0.287 mg/kg
	Soil	35 mg/kg

**8.2 Exposure controls**

**Engineering measures**

Handle only in a place equipped with local exhaust (or other appropriate exhaust).

**Personal protective equipment**

- Eye protection : Face-shield  
 Safety glasses with side-shields conforming to EN166
- Hand protection
- Material : Nitrile rubber
- Material : butyl-rubber
- Remarks : Protective gloves complying with EN 374.  
 The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. As the product is a mixture of several substances, the durability of the glove materials cannot be calculated in advance and has to be tested before use. The exact break through time can be obtained from the protective glove producer and this has to be observed.
- Skin and body protection : Chemical resistant apron  
 Long sleeved clothing
- Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Version: 2.5

Revision Date: 31.03.2020

Print Date: 01.04.2020

Recommended Filter type:  
ABEK-filter

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Protective measures : Follow the skin protection plan.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: yellow
Odour	: stinging
Odour Threshold	: No data available
pH	: 0.3 (20 °C) (undiluted)
Melting point/freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: 85 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: Upper flammability limit 38 %(V)
Lower explosion limit	: Lower flammability limit 1.3 %(V)
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: 1.05 g/cm <sup>3</sup> (20 °C) Method: DIN 51757
Solubility(ies) Water solubility	: 50 g/l
Solubility in other solvents	: No data available
Partition coefficient: n-	: No data available

Version: 2.5

Revision Date: 31.03.2020

Print Date: 01.04.2020

octanol/water

Auto-ignition temperature	:	435 °C
Decomposition temperature	:	No data available
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Flow time	:	No data available
Explosive properties	:	Vapours may form explosive mixture with air.
Oxidizing properties	:	No data available

## 9.2 Other information

Other physico-chemical properties: This information is not available/not determined.

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

### 10.4 Conditions to avoid

Conditions to avoid : Product is stable under appropriate usage.

### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

### 10.6 Hazardous decomposition products

Hazardous decomposition products : Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke.

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

##### Product:

Acute oral toxicity	:	Acute toxicity estimate: 977.31 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: 1.24 mg/l



Version: 2.5

Revision Date: 31.03.2020

Print Date: 01.04.2020

Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Calculation method

### **Acute toxicity**

#### **Components:**

##### **Benzyl alcohol:**

Acute oral toxicity : LD50 Oral (Rat): 1,230 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

##### **Formic Acid:**

Acute oral toxicity : LD50 (Rat): 730 mg/kg  
Method: OECD Test Guideline 401

##### **Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs.:**

Acute oral toxicity : LD50 (Rat): > 300 - 2,000 mg/kg  
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402

##### **1,3-Dibutyl-2-thiourea:**

Acute oral toxicity : LD50 (Rat): 350 mg/kg

### **Skin corrosion/irritation**

#### **Product:**

Remarks: Causes severe skin burns and eye damage.

### **Serious eye damage/eye irritation**

#### **Product:**

Remarks: Causes severe skin burns and eye damage.

### **Respiratory or skin sensitisation**

#### **Product:**

Remarks: This information is not available.

### **Germ cell mutagenicity**

#### **Product:**

Based on available data, the classification criteria are not met.

### **Carcinogenicity**

#### **Product:**

Version: 2.5

Revision Date: 31.03.2020

Print Date: 01.04.2020

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

### **Reproductive toxicity**

**Product:**

Based on available data, the classification criteria are not met.

### **STOT - single exposure**

**Product:**

Based on available data, the classification criteria are not met.

### **STOT - repeated exposure**

**Product:**

Based on available data, the classification criteria are not met.

### **Aspiration toxicity**

**Product:**

Based on available data, the classification criteria are not met.

### **Further information**

**Product:**

Remarks: According to many years of experience, there are no known harmful effects when handled properly.

Description of possible hazardous to health effects is based on experience and/or toxicological characteristics of several components.

---

## **SECTION 12: Ecological information**

### **12.1 Toxicity**

**Product:**

Ecotoxicology studies for the product are not available.

**Components:**

**Benzyl alcohol:**

- |   |   |   |
|---|---|---|
| Toxicity to fish                                    | : | LC50 (Fish): 460 mg/l<br>Exposure time: 96 h<br>Method: OECD Test Guideline 203   |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): 230 mg/l<br>Exposure time: 48 h<br>Method: OECD Test Guideline 202   |
| Toxicity to algae                                   | : | EC50 (Scenedesmus quadricauda (Green algae)): 79 mg/l<br>Exposure time: 3 h<br><br>EC0 (Scenedesmus quadricauda (Green algae)): 640 mg/l<br>Exposure time: 96 h |
| Toxicity to microorganisms                          | : | EC50 (Photobacterium phosphoreum): 71.42 mg/l<br>Exposure time: 30 min  |

Version: 2.5

Revision Date: 31.03.2020

Print Date: 01.04.2020

EC10 (*Pseudomonas putida*): 658 mg/l  
Exposure time: 16 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 51 mg/l  
Exposure time: 21 d  
Species: *Daphnia magna* (Water flea)  
Method: OECD Test Guideline 211

**Formic Acid:**

Toxicity to fish : LC50 (*Leuciscus idus* (Golden orfe)): > 46 - < 100 mg/l  
Exposure time: 96 h  
Test Type: static test

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): 34.2 mg/l  
Exposure time: 48 h

NOEC (*Daphnia magna* (Water flea)): >= 102 mg/l  
Exposure time: 21 d  
Test Type: static test

Toxicity to algae : EC50 (*Selenastrum capricornutum* (green algae)): 32.64 mg/l  
Exposure time: 72 h  
Test Type: static test

Toxicity to microorganisms : EC50 (*Pseudomonas putida*): 46.7 mg/l  
Exposure time: 17 h

**Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs.:**

Toxicity to fish : LC50 (*Lepomis macrochirus* (Bluegill sunfish)): > 1 - 10 mg/l  
Exposure time: 96 h  
Test Type: static test  
Test substance: Read-across (Analogy)

NOEC (*Lepomis macrochirus* (Bluegill sunfish)): 1 mg/l  
Exposure time: 28 d  
Test Type: Growth inhibition  
Test substance: Read-across (Analogy)

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): > 1 - 10 mg/l  
Exposure time: 48 h  
Test Type: static test  
Test substance: Read-across (Analogy)  
Method: OECD Test Guideline 202

NOEC (*Daphnia magna* (Water flea)): > 1 - 10 mg/l  
Exposure time: 32 d  
Test substance: Read-across (Analogy)

Toxicity to algae : NOEC (Algae): > 4 mg/l  
Exposure time: 28 d  
Test substance: Read-across (Analogy)

Version: 2.5

Revision Date: 31.03.2020

Print Date: 01.04.2020

## 12.2 Persistence and degradability

### Components:

#### **Formic Acid:**

Biochemical Oxygen Demand (BOD) : 86 mg/g

Chemical Oxygen Demand (COD) : 348 mg/g

#### **Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs.:**

Biodegradability : Test Type: aerobic  
Biodegradation: > 70 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301A  
Remarks: Readily biodegradable  
This surfactant complies with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

## 12.3 Bioaccumulative potential

### Product:

Bioaccumulation : Remarks: No data available

### Components:

#### **Benzyl alcohol:**

Partition coefficient: n-octanol/water : log Pow: 1.05

## 12.4 Mobility in soil

### Product:

Mobility : Remarks: No data available

## 12.5 Results of PBT and vPvB assessment

### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

## 12.6 Other adverse effects

### Product:

Additional ecological information : Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product	:	Dispose of in accordance with local regulations. Do not let product enter drains. Do not dispose of with domestic refuse.
Contaminated packaging	:	Dispose of in accordance with local regulations.
Waste Code	:	07 06 04 : other organic solvents, washing liquids and mother liquors

---

## SECTION 14: Transport information

### 14.1 UN number

ADR	:	UN 3412
RID	:	UN 3412
IMDG	:	UN 3412
IATA	:	UN 3412

### 14.2 UN proper shipping name

ADR	:	FORMIC ACID, MIXTURE
RID	:	FORMIC ACID, MIXTURE
IMDG	:	FORMIC ACID, MIXTURE
IATA	:	Formic acid, Mixture

### 14.3 Transport hazard class(es)

ADR	:	8
RID	:	8
IMDG	:	8
IATA	:	8

### 14.4 Packing group

<b>ADR</b>		
Packing group	:	II
Classification Code	:	C3
Hazard Identification Number	:	80
Labels	:	8
Tunnel restriction code	:	(E)

<b>RID</b>		
Packing group	:	II
Classification Code	:	C3
Hazard Identification Number	:	80
Labels	:	8

**IMDG**

**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
**K025-K60 COLOREX 2717**



Version: 2.5

Revision Date: 31.03.2020

Print Date: 01.04.2020

Packing group : II  
Labels : 8  
EmS Code : F-A, S-B  
Remarks : Acids, Clear of living quarters.

**IATA (Cargo)**

Packing instruction (cargo aircraft) : 855  
Packing instruction (LQ) : Y840  
Packing group : II  
Labels : Corrosives

**IATA (Passenger)**

Packing instruction (passenger aircraft) : 851  
Packing instruction (LQ) : Y840  
Packing group : II  
Labels : Corrosives

**14.5 Environmental hazards**

**ADR**

Environmentally hazardous : no

**RID**

Environmentally hazardous : no

**IMDG**

Marine pollutant : no

**14.6 Special precautions for user**

Refer to protective measures listed in sections 7 and 8.

**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable for product as supplied.

---

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Other regulations : The product is classified and labelled in accordance with EC directives or respective national laws.  
Regional or national implementations of GHS may not implement all hazard classes and categories.

**15.2 Chemical safety assessment**

A Chemical Safety Assessment is not required for this substance.

---

**SECTION 16: Other information**

**Full text of H-Statements**

H226 : Flammable liquid and vapour.  
H302 : Harmful if swallowed.  
H314 : Causes severe skin burns and eye damage.  
H318 : Causes serious eye damage.  
H319 : Causes serious eye irritation.  
H331 : Toxic if inhaled.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## K025-K60 COLOREX 2717



Version: 2.5

Revision Date: 31.03.2020

Print Date: 01.04.2020

H332 : Harmful if inhaled.  
H412 : Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Eye Dam. : Serious eye damage  
Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids  
Skin Corr. : Skin corrosion

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Other information : The information provided is based on our current knowledge and experience and apply to the product as delivered. Regarding the product properties, these are not guaranteed. The delivery of this safety datasheet does not free the recipient of the product from his own responsibility to follow the relevant rules and regulations concerning this product. This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

GB / EN