according to Regulation (EC) No. 1907/2006



Impulse für Mensch und Umwelt

## D593-AE4 hebro®sol A

Version: 1.7 Revision Date 04.08.2014 Print Date 24.12.2014

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : D593-AE4 hebro®sol A

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub
: Cleaner (solvent) for professional application in industry and

stance/Mixture trade

#### 1.3 Details of the supplier of the safety data sheet

Company : hebro chemie- ZN der Rockwood Specialties Group

GmbH

Rostocker Str. 40

41199 Mönchengladbach

Contact person : Wolfgang Schaffers
Telephone : +49 (0) 2166 6009-0
Telefax : +49 (0) 2166 6009-99

Contact person product safety Abteilung Produktsicherheit

E-mail address : info-produktsicherheit@gmx.de

#### 1.4 Emergency telephone number

: Giftinformationszentrum Erfurt:

+49 (0) 361 730 730

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour. Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single ex-

posure, Category 3

H319: Causes serious eye irritation. H336: May cause drowsiness or dizziness.

### Classification (67/548/EEC, 1999/45/EC)

Extremely flammable R12: Extremely flammable. Irritant R36: Irritating to eyes.

Harmful R66: Repeated exposure may cause skin dryness

or cracking.

R67: Vapours may cause drowsiness and dizzi-

ness.

according to Regulation (EC) No. 1907/2006



Impulse für Mensch und Umwelt

## D593-AE4 hebro®sol A

Version: 1.7 Revision Date 04.08.2014 Print Date 24.12.2014

#### 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

: EUH066 Repeated exposure may cause skin dry-

ness or cracking.

Precautionary statements : Prevention:

P210 Keep away from heat/sparks/open

flames/hot surfaces. - No smoking.

P211 Do not spray on an open flame or other

ignition source.

P233 Keep container tightly closed.

P243 Take precautionary measures against static

discharge.

P251 Do not pierce or burn, even after use.
P280 Wear protective gloves/ protective clothing/

o vvear protective gloves/ protective clothling

eve protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take

off immediately all contaminated clothing.

Rinse skin with water/ shower.

P304 + P340 IF INHALED: Remove victim to fresh air

and keep at rest in a position comfortable

for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with wa-

ter for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool. P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

• 67-64-1 Acetone

according to Regulation (EC) No. 1907/2006



Impulse für Mensch und Umwelt

## D593-AE4 hebro®sol A

Version: 1.7 Revision Date 04.08.2014 Print Date 24.12.2014

### Labelling according to EC Directives (67/548/EEC)

Hazard pictograms





Extremely flammable

Irritant

R-phrase(s) R12 Extremely flammable.

Irritating to eyes. R36

**R66** Repeated exposure may cause skin dry-

ness or cracking.

**R67** Vapours may cause drowsiness and dizzi-

ness.

S-phrase(s) : S23 Do not breathe spray, vapour,

> In case of contact with eyes, rinse immedi-S26

> > ately with plenty of water and seek medical

advice.

S29/56 Do not empty into drains, dispose of this

material and its container at hazardous or

special waste collection point.

If swallowed, seek medical advice immedi-**S46** 

ately and show this container or label.

S51 Use only in well-ventilated areas.

Special labelling of certain

mixtures

: Pressurized container. Protect from sunlight and do not ex-

pose to temperatures exceeding 50 °C.

Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Keep away from sources of ignition - No smoking.

Keep away from children.

#### 2.3 Other hazards

The information required is contained in this Material Safety Data Sheet.

## **SECTION 3: Composition/information on ingredients**

### 3.1 Substances

Not applicable

#### 3.2 Mixtures

Chemical nature : Preparation of hydrocarbons and other additives

#### **Hazardous components**

according to Regulation (EC) No. 1907/2006



Impulse für Mensch und Umwelt

## D593-AE4 hebro®sol A

Version: 1.7 Revision Date 04.08.2014 Print Date 24.12.2014

Chemical Name	CAS-No. EC-No. Registration num- ber	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
Acetone	67-64-1 200-662-2 01-2119471330-49	F; R11 Xi; R36 R66 R67	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	<= 100

For the full text of the R-phrases mentioned in this Section, see Section 16. For the full text of the H-Statements mentioned in this Section, see Section 16. For the full text of the Notas mentioned in this Section, see Section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice : Call a physician if symptoms occur.

If inhaled : Provide fresh air.

Keep patient warm and at rest.

If symptoms persist, call a physician.

In case of skin contact : Take off immediately all contaminated clothing.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

Do NOT use solvents or thinners.

In case of eye contact : Irrigate copiously with clean, fresh water for at least 10

minutes, holding the eyelids apart.

If eye irritation persists, consult a specialist.

If swallowed : Call a physician immediately.

Keep at rest.

Do NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No information available.

Risks : No information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

according to Regulation (EC) No. 1907/2006



Impulse für Mensch und Umwelt

## D593-AE4 hebro®sol A

Version: 1.7 Revision Date 04.08.2014 Print Date 24.12.2014

### SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or car-

bon dioxide.

Unsuitable extinguishing

media

: High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: Combustion may cause: Carbon dioxide (CO2) Carbon monoxide

#### 5.3 Advice for firefighters

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if nec-

essary

Further information : Use water spray to cool unopened containers.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Provide sufficient air exchange and/or exhaust in work rooms.

Remove all sources of ignition.

Do not breathe vapour.

Refer to protective measures listed in sections 7 and 8.

#### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

Inform the relevant authorities if it enters sewers, aquatic envi-

ronment or soil.

### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Contain spillage, soak up with non-combustible absorbent

material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local /

national regulations (see section 13).

Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

according to Regulation (EC) No. 1907/2006



Impulse für Mensch und Umwelt

## D593-AE4 hebro®sol A

Version: 1.7 Revision Date 04.08.2014 Print Date 24.12.2014

See chapter 8 and 13

### **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist.

When using do not eat, drink or smoke. For personal protection see section 8.

Take precautionary measures against static discharges. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn,

even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep away

from children.

Advice on protection against

fire and explosion

: Vapours are heavier than air and may spread along floors.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

: Electrical installations / working materials must comply with

the technological safety standards. Follow the water regulations.

Further information on stor-

age conditions

: Keep only in the original container in a cool, well-ventilated

place.

Keep away from sources of ignition - No smoking.

Keep away from heat.

Advice on common storage : Incompatible with oxidizing agents.

7.3 Specific end use(s)

Specific use(s) : Cleaner (solvent) for professional application in industry and

trade

### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

Components	CAS-No.	Value	Control pa- rameters	Update	Basis
Acetone	67-64-1	TWA	500 ppm 1,210 mg/m3	2009-12-19	2000/39/EC

according to Regulation (EC) No. 1907/2006



Impulse für Mensch und Umwelt

## D593-AE4 hebro®sol A

Version: 1.7 Revision Date 04.08.2014 Print Date 24.12.2014

Further infor- mation	: Indicative						
	67-64-1	TWA	500 ppm 1,210 mg/m3	2005-04-06	GB EH40		
	67-64-1	STEL	1,500 ppm 3,620 mg/m3	2005-04-06	GB EH40		

DNEL/DMEL

Acetone : End Use: DNEL, Workers

Exposure routes: Inhalation

Potential health effects: Short-term exposure, Systemic effects

Value: 1210 mg/m3

End Use: DNEL, Workers Exposure routes: Inhalation

Potential health effects: Long-term local effects

Value: 2420 mg/m3

End Use: DNEL, Workers Exposure routes: Inhalation

Potential health effects: Long-term systemic effects

Value: 1210 mg/m3

End Use: DNEL, Workers Exposure routes: Skin contact

Potential health effects: Long-term systemic effects

Value: 186 mg/kg

**PNEC** 

Acetone : Fresh water

Value: 10.6 mg/l

Marine water Value: 1.06 mg/l

Behaviour in waste water treatment plants

Value: 100 mg/l

Fresh water sediment

Value: 30.04 mg/kg dry weight (d.w.)

Marine sediment

Value: 3.04 mg/kg dry weight (d.w.)

according to Regulation (EC) No. 1907/2006



Impulse für Mensch und Umwelt

## D593-AE4 hebro®sol A

Version: 1.7 Revision Date 04.08.2014 Print Date 24.12.2014

Soil

Value: 29.5 mg/kg dry weight (d.w.)

#### 8.2 Exposure controls

### **Engineering measures**

Provide sufficient air exchange and/or exhaust in work rooms.

#### Personal protective equipment

Respiratory protection : Do not breathe gas/fumes/vapour/spray.

When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

Hand protection : Solvent-resistant gloves (butyl-rubber)

Protective gloves complying with EN 374.

The choice of an appropriate glove does not only depend on its material but also on other quality features and is different

from one producer to the other.

The exact break through time can be obtained from the pro-

tective glove producer and this has to be observed.

Eye protection : Safety glasses with side-shields

Skin and body protection : protective suit

Protective measures : Handle in accordance with good industrial hygiene and safety

practice.

Follow the skin protection plan.

#### **Environmental exposure controls**

General advice : Do not flush into surface water or sanitary sewer system.

Inform the relevant authorities if it enters sewers, aquatic envi-

ronment or soil.

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Appearance : aerosol

Colour : colourless

Odour : characteristic

Flash point : -18 °C

Ignition temperature : 465 °C

according to Regulation (EC) No. 1907/2006



D593-AE4 hebro®sol A

Version: 1.7 Revision Date 04.08.2014 Print Date 24.12.2014

Lower explosion limit : 2.6 %(V)

Upper explosion limit : 13 %(V)

pH : No data available

Boiling point/boiling range : 56 °C

Method: DIN 51751

Density : 0.79 g/cm3

at 20 °C

Method: DIN 51757

Water solubility : 1,000 g/l

completely soluble

9.2 Other information

Explosivity : In use, may form flammable/explosive vapour-air mixture.

### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No hazards to be specially mentioned.

#### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : No decomposition if used as directed.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

#### 10.6 Hazardous decomposition products

Risk of decomposition. : In case of fire hazardous decomposition products may be

produced such as:

according to Regulation (EC) No. 1907/2006



Impulse für Mensch und Umwelt

## D593-AE4 hebro®sol A

Version: 1.7 Revision Date 04.08.2014 Print Date 24.12.2014

Carbon dioxide (CO2) Carbon monoxide Nitrogen oxides (NOx)

Smoke

### **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

### **Acute toxicity**

Acute oral toxicity

Acetone : LD50: 5,800 mg/kg

Species: Rat

Method: OECD Test Guideline 401

Acute inhalation toxicity

Acetone : LC50: ca. 76 mg/l

Exposure time: 4 h Species: Rat

Acute dermal toxicity

Acetone : LD50: > 158,000 mg/kg

Species: Rabbit

Skin corrosion/irritation

Skin irritation : Repeated or prolonged contact with the mixture may cause

removal of natural fat from the skin resulting in desiccation of

the skin.

May cause eye and skin irritation.

Serious eye damage/eye irritation

Eye irritation : The liquid splashed in the eyes may cause irritation and re-

versible damage.

Respiratory or skin sensitisation

Sensitisation : This information is not available.

Germ cell mutagenicity

Acetone : Ames test

Result: negative

Method: OECD Test Guideline 471

according to Regulation (EC) No. 1907/2006



Impulse für Mensch und Umwelt

## D593-AE4 hebro®sol A

Version: 1.7 Revision Date 04.08.2014 Print Date 24.12.2014

Ames test

Result: negative

Method: OECD Test Guideline 476

Genotoxicity in vivo

Acetone : in vivo assay

Species: Mouse Oral

negative

Carcinogenicity

Remarks : Not classifiable as a human carcinogen.

**Further information** : Health injuries are not known or expected under normal use.

## **SECTION 12: Ecological information**

## 12.1 Toxicity

Toxicity to fish : No data available

Toxicity to fish

Acetone : static test LC50: 5,540 mg/l

Exposure time: 96 h

Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates

Acetone : static test EC50: 8,800 mg/l

Exposure time: 48 h

Species: Daphnia magna (Water flea)

flow-through test NOEC: 2,212 mg/l

Exposure time: 28 d

Species: Daphnia magna (Water flea)

Toxicity to algae

Acetone : static test NOEC: 430 mg/l

Exposure time: 96 h Species: Algae

static test NOEC: 530 mg/l

Exposure time: 8 d

according to Regulation (EC) No. 1907/2006



Impulse für Mensch und Umwelt

## D593-AE4 hebro®sol A

Version: 1.7 Revision Date 04.08.2014 Print Date 24.12.2014

Species: Microcystis aeruginosa

Toxicity to bacteria

Acetone : Respiration inhibition

.: 1,000 mg/l

Exposure time: 30 min Species: activated sludge

EC12

#### 12.2 Persistence and degradability

Biodegradability : No data available

## 12.3 Bioaccumulative potential

Bioaccumulation : No data available

### 12.4 Mobility in soil

Mobility : No data available

### 12.5 Results of PBT and vPvB assessment

No data available

#### 12.6 Other adverse effects

Additional ecological infor-

mation

: Do not flush into surface water or sanitary sewer system.

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

Do not let product enter drains.

Do not dispose of with domestic refuse.

Packaging : The hazard and precautionary statements displayed on the

label also apply to any residues left in the container.

Do not dispose of with domestic refuse.

Contaminated packaging : Dispose of in accordance with local regulations.

Waste Code : 160504 gases in pressure containers (including halons) con-

taining dangerous substances

according to Regulation (EC) No. 1907/2006



Impulse für Mensch und Umwelt

## D593-AE4 hebro®sol A

Version: 1.7 Revision Date 04.08.2014 Print Date 24.12.2014

### **SECTION 14: Transport information**

**ADR** 

**UN** number : 1950 UN proper shipping name Transport hazard class(es) : AEROSOLS

: 2 Classification Code : 5F Limited Quantity (LQ) Inner : 1.00 L

Packaging

Maximum quantity : 30.00 KG Labels : 2.1

Tunnel restriction code : (D) Environmentally hazardous : no

IATA

: 1950 **UN** number

Description of the goods : Aerosols, flammable

Class : 2.1 Labels : 2.1

IATA C

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203 Maximum quantity : 150.00 KG

Environmentally hazardous : no

IATA P

Packing instruction (passen-: 203

ger aircraft)

Packing instruction (LQ) : Y203 Maximum quantity : 75.00 KG

Environmentally hazardous : no

**IMDG** 

UN number : 1950

Description of the goods : AEROSOLS

Class : 2.1 Labels : 2.1 EmS Number 1 : F-D EmS Number 2 : S-U Marine pollutant

Shaded from sources of heat.

"IMDG-Code segregation group not applicable".

Shaded from sources of heat.

"IMDG-Code segregation group not applicable".

according to Regulation (EC) No. 1907/2006



Impulse für Mensch und Umwelt

## D593-AE4 hebro®sol A

Version: 1.7 Revision Date 04.08.2014 Print Date 24.12.2014

RID

UN number : 1950

Description of the goods : AEROSOLS

Transport hazard class(es) : 2
Classification Code : 5F
Hazard Identification Number : 23
Labels : 2.1
Limited Quantity (LQ) Inner : 1.00 L

**Packaging** 

Maximum quantity : 30.00 KG

Environmentally hazardous : no

#### **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations : The product is classified and labelled in accordance with EC

directives or respective national laws.

Regional or national implementations of GHS may not imple-

ment all hazard classes and categories.

#### 15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this substance.

### **SECTION 16: Other information**

### Full text of R-phrases referred to under sections 2 and 3

R11 Highly flammable.
R12 Extremely flammable.
R36 Irritating to eyes.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

#### Full text of H-Statements referred to under sections 2 and 3.

EUH066 Repeated exposure may cause skin dryness or cracking.

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

## **Further information**

The information provided is based on our current knowledge and experience and apply to the product

according to Regulation (EC) No. 1907/2006



Impulse für Mensch und Umwelt

## D593-AE4 hebro®sol A

Version: 1.7 Revision Date 04.08.2014 Print Date 24.12.2014

as delivered. Regarding the product properties, these are not guaranteed. The delivery of this safety datasheet does not free the recipient of the product from his own responsibility to follow the relevant rules and regulations concerning this product.

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.