

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

hebrochemie



Impulse für Mensch und Umwelt

## E604-AE2 hebro®lub KS

Version: 2.0

Revision Date 22.05.2015

Print Date 23.05.2015

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : E604-AE2 hebro®lub KS

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Special lubricant

#### 1.3 Details of the supplier of the safety data sheet

Company : hebro chemie- ZN der Rockwood Specialties Group  
GmbH  
Rostocker Str. 40  
41199 Mönchengladbach

Contact person : Wolfgang Schaffers  
Telephone : +49 (0) 2166 6009-0  
Telefax : +49 (0) 2166 6009-99

Contact person product safety : Abteilung Produktsicherheit  
Telephone : +49(0)2166 6009-176  
E-mail address : wolfgang.schaffers@chemetall.com

#### 1.4 Emergency telephone number

: Giftinformationszentrum Erfurt:  
+49 (0) 361 730 730

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3	H336: May cause drowsiness or dizziness.
Chronic aquatic toxicity, Category 3	H412: Harmful to aquatic life with long lasting effects.

##### Classification (67/548/EEC, 1999/45/EC)

Extremely flammable	R12: Extremely flammable. R67: Vapours may cause drowsiness and dizziness.
---------------------	---

## E604-AE2 hebro®lub KS

Version: 2.0

Revision Date 22.05.2015

Print Date 23.05.2015

ness.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : P102 Keep out of reach of children.  
**Prevention:**  
P260 Do not breathe spray.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P251 Do not pierce or burn, even after use.  
P211 Do not spray on an open flame or other ignition source.  
**Response:**  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
**Storage:**  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.  
**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

Labelling according to EC Directives (1999/45/EC)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

hebrochemie



Impulse für Mensch und Umwelt

## E604-AE2 hebro®lub KS

Version: 2.0

Revision Date 22.05.2015

Print Date 23.05.2015

Hazard pictograms



Extremely flammable

R-phrase(s)

: R12  
R67

Extremely flammable.  
Vapours may cause drowsiness and dizziness.

S-phrase(s)

: S23  
S60

Do not breathe spray.  
This material and its container must be disposed of as hazardous waste.

Special labelling of certain mixtures

: Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.  
Do not pierce or burn, even after use.  
Do not spray on a naked flame or any incandescent material.  
Keep away from sources of ignition - No smoking.  
Keep out of the reach of children.

### 2.3 Other hazards

The information required is contained in this Material Safety Data Sheet.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical nature : Preparation based on solvents and different solid lubricants

#### Hazardous components

Chemical Name	CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
Naphtha (petroleum), hydrotreated light		Xn; R65  Note H (Table 3.1), Note J	Asp. Tox. 1; H304	>= 10 - < 25
Acetone	67-64-1	F; R11	Flam. Liq. 2;	>= 15 - < 20

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

hebrochemie



Impulse für Mensch und Umwelt

## E604-AE2 hebro®lub KS

Version: 2.0

Revision Date 22.05.2015

Print Date 23.05.2015

	200-662-2 01-2119471330-49	Xi; R36  R66  R67	H225  Eye Irrit. 2; H319  STOT SE 3; H336	
Propane	74-98-6 200-827-9 01-2119486944-21	F+; R12	Flam. Gas 1; H220  Press. Gas Liquefied gas; H280	>= 10 - < 25
Hydrocarbons, C11 - C14, n-alkanes, isoal- kanes, cyclics, < 2 % aromatics	64742-47-8 926-141-6 01-2119456620-43	Xn; R65  R66	Asp. Tox. 1; H304	>= 1 - < 2.5

### Substances with a workplace exposure limit :

Butane	106-97-8 203-448-7 01-2119474691-32	F+; R12  Nota C	Flam. Gas 1; H220  Press. Gas Liquefied gas; H280	>= 10 - < 25
--------	---	-----------------------	--	--------------

For the full text of the R-phrases mentioned in this Section, see Section 16.  
For the full text of the H-Statements mentioned in this Section, see Section 16.  
For the full text of the Notas mentioned in this Section, see Section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Call a physician if symptoms occur.
- If inhaled : Provide fresh air.  
Keep patient warm and at rest.  
If symptoms persist, call a physician.
- In case of skin contact : Take off immediately all contaminated clothing.  
Wash skin thoroughly with soap and water or use recognized

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

hebrochemie



Impulse für Mensch und Umwelt

## E604-AE2 hebro®lub KS

Version: 2.0

Revision Date 22.05.2015

Print Date 23.05.2015

- skin cleanser.  
Do NOT use solvents or thinners.
- In case of eye contact : Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.  
If eye irritation persists, consult a specialist.
- If swallowed : Call a physician immediately.  
Keep at rest.  
Do NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No information available.
- Risks : No information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Combustion may cause:  
Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide

### 5.3 Advice for firefighters

- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Further information : Use water spray to cool unopened containers.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Provide sufficient air exchange and/or exhaust in work rooms.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

hebrochemie



Impulse für Mensch und Umwelt

## E604-AE2 hebro®lub KS

Version: 2.0

Revision Date 22.05.2015

Print Date 23.05.2015

Remove all sources of ignition.  
Do not breathe vapour.  
Refer to protective measures listed in sections 7 and 8.

### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system. Inform the relevant authorities if it enters sewers, aquatic environment or soil.

### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

See chapter 8 and 13

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist.  
When using do not eat, drink or smoke.  
For personal protection see section 8.  
Take precautionary measures against static discharges.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.  
Do not spray on a naked flame or any incandescent material.  
Keep away from sources of ignition - No smoking. Keep away from children.

Advice on protection against fire and explosion : Vapours are heavier than air and may spread along floors.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Electrical installations / working materials must comply with the technological safety standards.  
Follow the water regulations.

Further information on storage conditions : Keep only in the original container in a cool, well-ventilated place.  
Keep away from sources of ignition - No smoking.  
Keep away from heat.

Advice on common storage : Incompatible with oxidizing agents.

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

**hebrochemie**

Impulse für Mensch und Umwelt

**E604-AE2 hebro®lub KS**

Version: 2.0

Revision Date 22.05.2015

Print Date 23.05.2015

**7.3 Specific end use(s)**

Specific use(s) : Special lubricant

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters**

Components	CAS-No.	Value	Control parameters	Update	Basis
Acetone	67-64-1	TWA	500 ppm 1,210 mg/m <sup>3</sup>	2009-12-19	2000/39/EC
Further information	:	Indicative			
	67-64-1	TWA	500 ppm 1,210 mg/m <sup>3</sup>	2005-04-06	GB EH40
	67-64-1	STEL	1,500 ppm 3,620 mg/m <sup>3</sup>	2005-04-06	GB EH40
Butane	106-97-8	TWA	600 ppm 1,450 mg/m <sup>3</sup>	2007-08-01	GB EH40
Further information	:	Carc: Capable of causing cancer and/or heritable genetic damage. The identified substances include those which: - are assigned the risk phrases 'R45: May cause cancer'; 'R46: may cause heritable genetic damage'; 'R49: May cause cancer by inhalation' or - a substance or process listed in Schedule 1 of COSHH. Carcinogenic only applies if butane contains more than 0.1% of buta-1,3-diene			
	106-97-8	STEL	750 ppm 1,810 mg/m <sup>3</sup>	2007-08-01	GB EH40
Further information	:	Carc: Capable of causing cancer and/or heritable genetic damage. The identified substances include those which: - are assigned the risk phrases 'R45: May cause cancer'; 'R46: may cause heritable genetic damage'; 'R49: May cause cancer by inhalation' or - a substance or process listed in Schedule 1 of COSHH. Carcinogenic only applies if butane contains more than 0.1% of buta-1,3-diene			

DNEL/DMEL

Acetone : End Use: Workers DNEL

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

hebrochemie



Impulse für Mensch und Umwelt

## E604-AE2 hebro®lub KS

Version: 2.0

Revision Date 22.05.2015

Print Date 23.05.2015

Exposure routes: Inhalation  
Potential health effects: Long-term systemic effects  
Value: 1210 mg/m<sup>3</sup>

End Use: Workers DNEL  
Exposure routes: Inhalation  
Potential health effects: Long-term local effects  
Value: 2420 mg/m<sup>3</sup>

End Use: Workers DNEL  
Exposure routes: Inhalation  
Potential health effects: Acute systemic effects  
Value: 1210 mg/m<sup>3</sup>

End Use: Workers DNEL  
Exposure routes: Skin contact  
Potential health effects: Long-term systemic effects  
Value: 186 mg/kg bw/day

PNEC  
Acetone

: Fresh water  
Value: 10.6 mg/l

Marine water  
Value: 1.06 mg/l

Sewage treatment plant  
Value: 100 mg/l

Fresh water sediment  
Value: 30.04 mg/kg dry weight (d.w.)

Marine sediment  
Value: 3.04 mg/kg dry weight (d.w.)

Soil  
Value: 29.5 mg/kg dry weight (d.w.)

### 8.2 Exposure controls

#### Engineering measures

Provide sufficient air exchange and/or exhaust in work rooms.

#### Personal protective equipment

Respiratory protection : Do not breathe gas/fumes/vapour/spray.  
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection : Chemical resistant gloves made of butyl rubber or nitrile rub-



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

hebrochemie



Impulse für Mensch und Umwelt

## E604-AE2 hebro®lub KS

Version: 2.0

Revision Date 22.05.2015

Print Date 23.05.2015

ber category III according to EN 374.

Eye protection : Safety glasses with side-shields

Skin and body protection : protective suit

Protective measures : Handle in accordance with good industrial hygiene and safety practice.  
Follow the skin protection plan.

### Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.  
Inform the relevant authorities if it enters sewers, aquatic environment or soil.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : aerosol

Colour : white

Odour : characteristic

Flash point : 11 °C

Lower explosion limit : 1.5 %(V)

Upper explosion limit : 9.5 %(V)

pH : Not applicable

Density : 1.00 g/cm<sup>3</sup>  
at 20 °C  
Method: DIN 51757

Water solubility : partly soluble

### 9.2 Other information

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

hebrochemie



Impulse für Mensch und Umwelt

## E604-AE2 hebro®lub KS

Version: 2.0

Revision Date 22.05.2015

Print Date 23.05.2015

Explosivity : In use, may form flammable/explosive vapour-air mixture.

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No hazards to be specially mentioned.

#### 10.2 Chemical stability

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

#### 10.4 Conditions to avoid

Conditions to avoid : No decomposition if used as directed.

#### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

#### 10.6 Hazardous decomposition products

Risk of decomposition. : In case of fire hazardous decomposition products may be produced such as:  
Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide  
Nitrogen oxides (NO<sub>x</sub>)  
Smoke

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity

##### Acute oral toxicity

Acetone : LD50: 5,800 mg/kg  
Species: Rat  
Method: OECD Test Guideline 401

##### Acute inhalation toxicity

Acetone : LC50: ca. 76 mg/l  
Exposure time: 4 h  
Species: Rat

##### Acute dermal toxicity

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

hebrochemie



Impulse für Mensch und Umwelt

## E604-AE2 hebro®lub KS

Version: 2.0

Revision Date 22.05.2015

Print Date 23.05.2015

Acetone : LD50: > 158,000 mg/kg  
Species: Rabbit

### Skin corrosion/irritation

Skin irritation : Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin.  
May cause eye and skin irritation.

### Serious eye damage/eye irritation

Eye irritation : The liquid splashed in the eyes may cause irritation and reversible damage.

### Respiratory or skin sensitisation

Sensitisation : This information is not available.

### Germ cell mutagenicity

Acetone : Ames test  
Result: negative  
Method: OECD Test Guideline 471  
  
Ames test  
Result: negative  
Method: OECD Test Guideline 476

### Genotoxicity in vivo

Acetone : in vivo assay  
Species: Mouse Oral  
negative

### Carcinogenicity

Remarks : Not classifiable as a human carcinogen.

**Further information** : Health injuries are not known or expected under normal use.

## SECTION 12: Ecological information

### 12.1 Toxicity

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

hebrochemie



Impulse für Mensch und Umwelt

## E604-AE2 hebro®lub KS

Version: 2.0

Revision Date 22.05.2015

Print Date 23.05.2015

Toxicity to fish : No data available

Toxicity to fish  
Acetone : static test LC50: 5,540 mg/l  
Exposure time: 96 h  
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates  
Acetone : static test EC50: 8,800 mg/l  
Exposure time: 48 h  
Species: Daphnia magna (Water flea)  
  
flow-through test NOEC: 2,212 mg/l  
Exposure time: 28 d  
Species: Daphnia magna (Water flea)

Toxicity to algae  
Acetone : static test NOEC: 430 mg/l  
Exposure time: 96 h  
Species: Algae  
  
static test NOEC: 530 mg/l  
Exposure time: 8 d  
Species: Microcystis aeruginosa

Toxicity to bacteria  
Acetone : Respiration inhibition  
.: 1,000 mg/l  
Exposure time: 30 min  
Species: activated sludge  
EC12

### 12.2 Persistence and degradability

Biodegradability : No data available

### 12.3 Bioaccumulative potential

Bioaccumulation : No data available

### 12.4 Mobility in soil

Mobility : No data available

### 12.5 Results of PBT and vPvB assessment

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

hebrochemie



Impulse für Mensch und Umwelt

## E604-AE2 hebro®lub KS

Version: 2.0

Revision Date 22.05.2015

Print Date 23.05.2015

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

Additional ecological information : Do not flush into surface water or sanitary sewer system.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.  
Do not let product enter drains.  
Do not dispose of with domestic refuse.

Packaging : The hazard and precautionary statements displayed on the label also apply to any residues left in the container.  
Do not dispose of with domestic refuse.

Contaminated packaging : Dispose of in accordance with local regulations.

Waste Code : 160504 gases in pressure containers (including halons) containing dangerous substances

## SECTION 14: Transport information

### ADR

UN number : 1950  
UN proper shipping name : AEROSOLS  
Transport hazard class(es) : 2  
Classification Code : 5F  
Limited Quantity (LQ) Inner : 1.00 L  
Packaging  
Maximum quantity : 30.00 KG  
Labels : 2.1  
Tunnel restriction code : (D)  
Environmentally hazardous : no

### IATA

UN number : 1950  
Description of the goods : Aerosols, flammable  
Class : 2.1  
Labels : 2.1

### IATA\_C

Packing instruction (cargo aircraft) : 203  
Packing instruction (LQ) : Y203

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

hebrochemie



Impulse für Mensch und Umwelt

## E604-AE2 hebro®lub KS

Version: 2.0

Revision Date 22.05.2015

Print Date 23.05.2015

Maximum quantity : 150.00 KG  
Environmentally hazardous : no

### IATA\_P

Packing instruction (passenger aircraft) : 203  
Packing instruction (LQ) : Y203  
Maximum quantity : 75.00 KG  
Environmentally hazardous : no

### IMDG

UN number : 1950  
Description of the goods : AEROSOLS  
Class : 2.1  
Labels : 2.1  
EmS Number 1 : F-D  
EmS Number 2 : S-U  
Marine pollutant : no

**Shaded from sources of heat.**

**"IMDG-Code segregation group not applicable".**

**Shaded from sources of heat.**

**"IMDG-Code segregation group not applicable".**

### RID

UN number : 1950  
Description of the goods : AEROSOLS  
Transport hazard class(es) : 2  
Classification Code : 5F  
Hazard Identification Number : 23  
Labels : 2.1  
Limited Quantity (LQ) Inner : 1.00 L  
Packaging  
Maximum quantity : 30.00 KG

Environmentally hazardous : no

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations : The product is classified and labelled in accordance with EC directives or respective national laws.  
Regional or national implementations of GHS may not implement all hazard classes and categories.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

hebrochemie



Impulse für Mensch und Umwelt

## E604-AE2 hebro®lub KS

Version: 2.0

Revision Date 22.05.2015

Print Date 23.05.2015

### 15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this substance.

### SECTION 16: Other information

#### Full text of R-phrases referred to under sections 2 and 3

R11	Highly flammable.
R12	Extremely flammable.
R36	Irritating to eyes.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

#### Full text of H-Statements referred to under sections 2 and 3.

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

#### Full text of Notas referred to under section 3

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

hebrochemie



Impulse für Mensch und Umwelt

## E604-AE2 hebro®lub KS

Version: 2.0

Revision Date 22.05.2015

Print Date 23.05.2015

**Nota C** Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In Annex I, a general designation of the following type is sometimes used: "xylenol". In this case the manufacturer or any other person who markets such a substance must state on the label whether the substance is a specific isomer (a) or a mixture of isomers (b). Example: (a) 2,4-dimethylphenol (b) xylenol (mixture of isomers).

**Note H (Table 3.1)** The classification and labelling shown for this substance applies to the hazardous property(ies) indicated by the hazard statement(s) in combination with the hazard class(es) and category(ies) shown. The requirements of Article 4 for manufacturers, importers or downstream users of this substance apply to all other hazard classes and categories. For hazard classes where the route of exposure or the nature of the effects leads to a differentiation of the classification of the hazard class, the manufacturer, importer or downstream user is required to consider the routes of exposure or the nature of the effects not already considered. The final label shall follow the requirements of Article 17 and of section 1.2 of Annex I.

**Note J** The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). This note applies only to certain complex coal- and oil-derived substances in Part 3.

### Further information

The information provided is based on our current knowledge and experience and apply to the product as delivered. Regarding the product properties, these are not guaranteed. The delivery of this safety datasheet does not free the recipient of the product from his own responsibility to follow the relevant rules and regulations concerning this product.

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.