according to Regulation (EC) No. 1907/2006

REPAL 2000 (5 kg) (Aluminium-Eloxal-Reiniger)



Version: 1.7 Revision Date: 15.06.2023 Print Date: 16.06.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : REPAL 2000 (5 kg) (Aluminium-Eloxal-Reiniger)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Cleaner for professional application in industry and trade

stance/Mixture

Contact person Telephone

Telefax

1.3 Details of the supplier of the safety data sheet

Company : hebro chemie- ZN der Rockwood Specialties Group

GmbH

Rostocker Str. 40

41199 Mönchengladbach : Zentrale hebro chemie : +49 (0) 2166 6009-0 : +49 (0) 2166 6009-99

Contact person product safety
Telephone
: +49(0)2166 6009-311
E-mail address
: msds.de@hebro-chemie.de

1.4 Emergency telephone number

: Giftinformationszentrum Erfurt:

+49 (0) 361 730 730

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

Precautionary statements : **Prevention**:

P261 Avoid breathing mist or vapours.

according to Regulation (EC) No. 1907/2006

REPAL 2000 (5 kg) (Aluminium-Eloxal-Reiniger)



Version: 1.7 Revision Date: 15.06.2023 Print Date: 16.06.2023

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

2-Methyl-2H-isothiazol-3-one

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Cleaning agent

Components

Chemical name 2-Methyl-2H-isothiazol-3-one	CAS-No. EC-No. Index-No. Registration number 2682-20-4 220-239-6	M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1 specific concentration limit Skin Sens. 1A; H317 >= 0.0015 %	Concentration (% w/w) >= 0.0015 - < 0.1			
Substances with a workplace exposure limit :						
Aluminium oxide	1344-28-1		>= 1 - < 2.5			
	215-691-6		. 12.0			
Francisco Constalla de Constall	01-2119529248-35					

For explanation of abbreviations see section 16.

according to Regulation (EC) No. 1907/2006

REPAL 2000 (5 kg) (Aluminium-Eloxal-Reiniger)



Version: 1.7 Revision Date: 15.06.2023 Print Date: 16.06.2023

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled : Move to fresh air.

If symptoms persist, call a physician.

In case of skin contact : Take off all contaminated clothing immediately.

After contact with skin, wash immediately with plenty of soap

and water.

In case of eye contact : In case of eye contact, remove contact lens and rinse imme-

diately with plenty of water, also under the eyelids, for at least

15 minutes.

If eye irritation persists, consult a specialist.

If swallowed : Rinse mouth with water.

Never give anything by mouth to an unconscious person.

Do NOT induce vomiting.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No information available.

Risks : No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Alcohol-resistant foam Carbon dioxide (CO2)

Dry powder Water spray jet

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Hazardous decomposition products formed under fire condi-

tions

Carbon dioxide (CO2) Carbon monoxide

5.3 Advice for firefighters

Special protective equipment :

for firefighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

according to Regulation (EC) No. 1907/2006

REPAL 2000 (5 kg) (Aluminium-Eloxal-Reiniger)



Version: 1.7 Revision Date: 15.06.2023 Print Date: 16.06.2023

Further information : Use water spray to cool unopened containers.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Wear suitable protective clothing, gloves and eye/face protec-

tion.

6.2 Environmental precautions

Environmental precautions : Inform the relevant authorities if it enters sewers, aquatic envi-

ronment or soil.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, soak up with non-combustible absorbent

material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local /

national regulations (see section 13).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Provide sufficient air exchange and/or exhaust in work rooms.

Have eye wash bottle or eye rinse ready at the work place.

Avoid contact with skin and eyes.

Product is used in dilutions with water

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Keep in a well-ventilated

place.

Advice on common storage : No materials to be especially mentioned.

7.3 Specific end use(s)

Specific use(s) : Cleaner for professional application in industry and trade

according to Regulation (EC) No. 1907/2006

REPAL 2000 (5 kg) (Aluminium-Eloxal-Reiniger)



Version: 1.7 Revision Date: 15.06.2023 Print Date: 16.06.2023

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis		
Aluminium oxide	1344-28-1	TWA (inhalable	10 mg/m3	GB EH40		
	Further information: For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols., The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the					
		osure limit should be TWA (Respirable		GB EH40		
		dust)				
	halable dust a sampling is ur MDHS14/4 Geble, thoracic a hazardous to in air equal to mg.m-3 8-hou ject to COSH have been as the appropriat of sizes. The lentry into the depend on the fractions for libel dust approand mouth durespiratory trato the gas examaterial are g	are those fractions of indertaken in accordate eneral methods for some indertaken in accordate eneral methods for some indertaken in accordate eneral methods for some indext or greater than 10 more TWA of respirable. If people are expossigned specific WEL is limits., Most industrial end size of indext indext energy indext energy some indext indext energy indext in accordance in the fraction of the indext indext energy in the	ses of these limits, respirable airborne dust which will be of ince with the methods descripant ampling and gravimetric anals., The COSHH definition of of any kind when present at ang.m-3 8-hour TWA of inhala dust. This means that any dot sed to dust above these leves and exposure to these must trial dusts contain particles of any particular paystem, and the body responsite termed 'inhalable' and 'respiration of airborne material that externed 'inhalable' and 'respiration of airborne material that externed the composition of the compo	collected when bed in lysis or respira- a substance a concentration ble dust or 4 ust will be subles. Some dusts at comply with f a wide range article after se that it elicits, es two size rable'., Inhalanters the nose sition in the hat penetrates xplanatory nents that have		

according to Regulation (EC) No. 1907/2006

REPAL 2000 (5 kg) (Aluminium-Eloxal-Reiniger)



Version: 1.7 Revision Date: 15.06.2023 Print Date: 16.06.2023

Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
White mineral oil	Workers	Inhalation	Long-term systemic effects	2.7 mg/m3
	Workers	Skin contact	Long-term systemic effects	1 mg/kg bw/day
Stearic acid, pure	Workers	Inhalation	Long-term systemic effects	17.63 mg/m3
Aluminium oxide	Workers	Inhalation	Long-term local ef- fects	15.63 mg/m3

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Safety glasses with side-shields

Hand protection

Material : Chemical resistant gloves made of butyl rubber or nitrile rub-

ber category III according to EN 374.

Remarks : The choice of an appropriate glove does not only depend on

its material but also on other quality features and is different from one producer to the other. The exact break through time can be obtained from the protective glove producer and this

has to be observed.

Skin and body protection : Long sleeved clothing

Respiratory protection : Breathing apparatus needed only when aerosol or mist is

formed.

Filter type : ABEK-filter

Protective measures : Follow the skin protection plan.

Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : white

Odour : characteristic

Melting point/range : not determined

Initial boiling point and boiling :

range

ca. 100 °C

Upper explosion limit / Upper : 6.0 %(V)

according to Regulation (EC) No. 1907/2006

REPAL 2000 (5 kg) (Aluminium-Eloxal-Reiniger)



Version: 1.7 Revision Date: 15.06.2023 Print Date: 16.06.2023

flammability limit

Lower explosion limit / Lower : 0.6 %(V)

flammability limit

Flash point Not applicable

Auto-ignition temperature not determined

рΗ ca. 6 (20 °C)

Viscosity

Viscosity, kinematic > 21 mm²/s (40 °C)

Solubility(ies)

Water solubility soluble

Partition coefficient: n-

octanol/water

Not applicable

Vapour pressure not determined

Density ca. 0.94 g/cm³ (20 °C)

Relative vapour density not determined

9.2 Other information

Explosives Vapours may form explosive mixture with air.

Self-ignition not auto-flammable

Substances and mixtures. which in contact with water, emit flammable gases

no explosion risk

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable at normal ambient temperature and pressure.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid Product is stable under appropriate usage.

10.5 Incompatible materials

Materials to avoid None known.

according to Regulation (EC) No. 1907/2006

REPAL 2000 (5 kg) (Aluminium-Eloxal-Reiniger)



Revision Date: 15.06.2023 Version: 1.7 Print Date: 16.06.2023

10.6 Hazardous decomposition products

Carbon monoxide Carbon dioxide (CO2)

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Components:

Aluminium oxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Skin corrosion/irritation

Product:

Remarks Moderate skin irritation

Serious eye damage/eye irritation

Product:

Remarks Irritant effects are possible.

Respiratory or skin sensitisation

Product:

Remarks May cause an allergic skin reaction.

Carcinogenicity

Product:

Carcinogenicity - Assess- : Not classifiable as a human carcinogen.

ment

11.2 Information on other hazards

Further information

Product:

Remarks Has a degreasing effect on the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

2-Methyl-2H-isothiazol-3-one:

M-Factor (Acute aquatic tox- : 10

icity)

according to Regulation (EC) No. 1907/2006

REPAL 2000 (5 kg) (Aluminium-Eloxal-Reiniger)



Version: 1.7 Revision Date: 15.06.2023 Print Date: 16.06.2023

Toxicity to microorganisms : EC20 (activated sludge): 2.8 mg/l

Exposure time: 3 h Method: DIN 38412

EC50 (activated sludge): 34.6 mg/l

Exposure time: 3 h Method: DIN 38412

M-Factor (Chronic aquatic

toxicity)

: 1

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: The surfactants contained in this preparation com-

ply with the biodegradability criteria as laid down in Regulation

(EC) No.907/2006 on detergents.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

Do not flush into surface water or sanitary sewer system.

Avoid subsoil penetration.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not let product enter drains.

Do not dispose of with domestic refuse.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

according to Regulation (EC) No. 1907/2006

REPAL 2000 (5 kg) (Aluminium-Eloxal-Reiniger)



Version: 1.7 Revision Date: 15.06.2023 Print Date: 16.06.2023

Contaminated packaging : Dispose of in accordance with local regulations.

Waste Code : Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA_P : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA_P : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA_P : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA_P (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Regulation (EC) No. 1907/2006

REPAL 2000 (5 kg) (Aluminium-Eloxal-Reiniger)



Version: 1.7 Revision Date: 15.06.2023 Print Date: 16.06.2023

UK REACH List of substances subject to authorisation

(Annex XIV)

: Not applicable

UK REACH Candidate list of substances of very high

concern (SVHC) for Authorisation

Not applicable

The Persistent Organic Pollutants Regulations (retained

Regulation (EU) 2019/1021 as amended for Great Brit-

: Not applicable

ain)

Other regulations:

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of other abbreviations

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

according to Regulation (EC) No. 1907/2006

REPAL 2000 (5 kg) (Aluminium-Eloxal-Reiniger)



Version: 1.7 Revision Date: 15.06.2023 Print Date: 16.06.2023

Other information :

The information provided is based on our current knowledge and experience and apply to the product as delivered. Regarding the product properties, these are not guaranteed. The delivery of this safety datasheet does not free the recipient of the product from his own responsibility to follow the relevant rules and regulations concerning this product.

This safety datasheet complies with the requirements of

Regulation (EC) No. 1907/2006.

Classification of the mixture:

Classification procedure:

Skin Sens. 1 H317 Calculation method

GB/EN