

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorstift B.K.-2/3, 12 ml (mittelbronze (C33))



A brand of BASF – we create chemistry

Version: 1.5

Revision Date: 10.10.2024

Print Date: 11.10.2024

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name : Colorstift B.K.-2/3, 12 ml (mittelbronze (C33))

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Special finishes

### 1.3 Details of the supplier of the safety data sheet

Company : hebro chemie- ZN der Rockwood Specialties Group  
GmbH  
Rostocker Str. 40  
41199 Mönchengladbach

Contact person : Zentrale hebro chemie  
Telephone : +49 (0) 2166 6009-0  
Telefax : +49 (0) 2166 6009-99

Contact person product safety : Abteilung Produktsicherheit  
Telephone : +49(0)2166 6009-311  
E-mail address : msds.de@hebro-chemie.de

### 1.4 Emergency telephone number

: Giftinformationszentrum Erfurt:  
+49 (0) 361 730 730

---

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

|  |  |
|--|--|
| Flammable liquids, Category 3  | H226: Flammable liquid and vapour.                     |
| Specific target organ toxicity - single exposure, Category 3, Central nervous system | H336: May cause drowsiness or dizziness.               |
| Specific target organ toxicity - single exposure, Category 3, Respiratory system     | H335: May cause respiratory irritation.                |
| Long-term (chronic) aquatic hazard, Category 2                                       | H411: Toxic to aquatic life with long lasting effects. |

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorstift B.K.-2/3, 12 ml (mittelbronze (C33))

Version: 1.5

Revision Date: 10.10.2024

Print Date: 11.10.2024

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing mist or vapours.  
P273 Avoid release to the environment.  
**Response:**  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.  
P391 Collect spillage.

### Hazardous components which must be listed on the label:

Hydrocarbons, C9, aromatics  
2-Methoxy-1-methylethyl acetate  
Xylene  
n-Butyl acetate

### Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

## 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

Toxicological information: This substance/mixture does not contain components considered to have endocrine disrupting properties for human health according to UK REACH Article 57(f).

---

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Mixture

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorstift B.K.-2/3, 12 ml (mittelbronze (C33))

Version: 1.5

Revision Date: 10.10.2024

Print Date: 11.10.2024

### Components

| Chemical name                   | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number     | Classification   | Concentration<br>(% w/w) |
|---------------------------------|---|--|--------------------------|
| Hydrocarbons, C9, aromatics     | Not Assigned<br><br>01-2119455851-35                      | Flam. Liq. 3; H226<br>STOT SE 3; H335,<br>H336<br>Asp. Tox. 1; H304<br>Aquatic Chronic 2;<br>H411  | >= 25 - < 50             |
| 2-Methoxy-1-methylethyl acetate | 108-65-6<br>203-603-9<br>01-2119475791-29                 | Flam. Liq. 3; H226<br>STOT SE 3; H336<br>(Central nervous<br>system)   | >= 10 - < 20             |
| Xylene                          | 1330-20-7<br><br>01-2119488216-32                         | Flam. Liq. 3; H226<br>Acute Tox. 4; H332<br>Acute Tox. 4; H312<br>Skin Irrit. 2; H315<br>Eye Irrit. 2; H319<br>STOT SE 3; H335<br>(Respiratory system)<br>STOT RE 2; H373<br>Asp. Tox. 1; H304<br>Aquatic Chronic 3;<br>H412 | >= 2.5 - < 10            |
| n-Butyl acetate                 | 123-86-4<br>204-658-1<br>607-025-00-1<br>01-2119485493-29 | Flam. Liq. 3; H226<br>STOT SE 3; H336<br>(Central nervous<br>system)<br>EUH066   | >= 2.5 - < 10            |
| titanium dioxide                | 13463-67-7<br>236-675-5<br>01-2119489379-17               | Carc. 2; H351<br>Aquatic Chronic 3;<br>H412  | >= 1 - < 2.5             |

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : Provide fresh air.  
Keep patient warm and at rest.
- In case of skin contact : Take off all contaminated clothing immediately.  
After contact with skin, wash immediately with plenty of soap and water.
- In case of eye contact : In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorstift B.K.-2/3, 12 ml (mittelbronze (C33))

Version: 1.5

Revision Date: 10.10.2024

Print Date: 11.10.2024

If swallowed : Call a physician immediately.  
Do NOT induce vomiting.  
Rinse mouth with water.  
Immediately give large quantities of water to drink.  
Provide fresh air.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No information available.  
Risks : May cause respiratory irritation.  
May cause drowsiness or dizziness.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.  
For specialist advice physicians should contact the Poisons  
Information Service.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry powder  
Water spray jet

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Hazardous decomposition products formed under fire conditions.  
Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Specific extinguishing methods : Use water spray to cool unopened containers.  
Suppress (knock down) gases/vapours/mists with a water spray jet.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Ensure adequate ventilation.  
Do not breathe vapours, aerosols.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorstift B.K.-2/3, 12 ml (mittelbronze (C33))

Version: 1.5

Revision Date: 10.10.2024

Print Date: 11.10.2024

### 6.2 Environmental precautions

Environmental precautions : Inform the relevant authorities if it enters sewers, aquatic environment or soil.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8., For disposal considerations see section 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Keep away from open flames, hot surfaces and sources of ignition.  
Take precautionary measures against static discharges.  
For personal protection see section 8.

Advice on protection against fire and explosion : Vapours are heavier than air and may spread along floors.  
Vapours may form explosive mixtures with air.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Follow the water regulations. Keep only in the original container in a cool, well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Further information on storage conditions : Keep container tightly closed. Keep only in the original container in a cool, well-ventilated place. Keep away from heat. Keep away from sources of ignition - No smoking. Keep at temperatures between - 7°C and 40°C.

Advice on common storage : Incompatible with oxidizing agents.

### 7.3 Specific end use(s)

Specific use(s) : Lacquer

---

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|------------|---------|-------------------------------|--------------------|-------|
|------------|---------|-------------------------------|--------------------|-------|

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorstift B.K.-2/3, 12 ml (mittelbronze (C33))

Version: 1.5

Revision Date: 10.10.2024

Print Date: 11.10.2024

|                                 |  |                       |                                  |         |
|---------------------------------|--|-----------------------|----------------------------------|---------|
| 2-Methoxy-1-methylethyl acetate | 108-65-6   | TWA                   | 50 ppm<br>274 mg/m <sup>3</sup>  | GB EH40 |
|                                 | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |                       |                                  |         |
|                                 |  | STEL                  | 100 ppm<br>548 mg/m <sup>3</sup> | GB EH40 |
|                                 | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |                       |                                  |         |
| Xylene                          | 1330-20-7  | TWA                   | 50 ppm<br>220 mg/m <sup>3</sup>  | GB EH40 |
|                                 | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |                       |                                  |         |
|                                 |  | STEL                  | 100 ppm<br>441 mg/m <sup>3</sup> | GB EH40 |
|                                 | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |                       |                                  |         |
| n-Butyl acetate                 | 123-86-4   | TWA                   | 150 ppm<br>724 mg/m <sup>3</sup> | GB EH40 |
|                                 |  | STEL                  | 200 ppm<br>966 mg/m <sup>3</sup> | GB EH40 |
| titanium dioxide                | 13463-67-7   | TWA (inhalable dust)  | 10 mg/m <sup>3</sup>             | GB EH40 |
|                                 |  | TWA (Respirable dust) | 4 mg/m <sup>3</sup>              | GB EH40 |

### Biological occupational exposure limits

| Substance name | CAS-No.   | Control parameters   | Sampling time | Basis          |
|----------------|-----------|--|---------------|----------------|
| Xylene         | 1330-20-7 | methyl hippuric acid: 650 Millimoles per mole creatinine (Urine) | After shift   | GB EH40<br>BAT |

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

| Substance name                  | End Use | Exposure routes | Potential health effects   | Value                 |
|---------------------------------|---------|-----------------|----------------------------|-----------------------|
| Hydrocarbons, C9, aromatics     | Workers | Inhalation      | Long-term systemic effects | 150 mg/m <sup>3</sup> |
|                                 | Workers | Skin contact    | Long-term systemic effects | 25 mg/kg bw/day       |
| 2-Methoxy-1-methylethyl acetate | Workers | Inhalation      | Long-term systemic effects | 275 mg/m <sup>3</sup> |
|                                 | Workers | Skin contact    | Long-term systemic effects | 153.5 mg/kg bw/day    |
| Xylene                          | Workers | Inhalation      | Long-term systemic effects | 77 mg/m <sup>3</sup>  |
| n-Butyl acetate                 | Workers | Inhalation      | Long-term systemic effects | 480 mg/m <sup>3</sup> |
|                                 | Workers | Inhalation      | Long-term local effects    | 480 mg/m <sup>3</sup> |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorstift B.K.-2/3, 12 ml (mittelbronze (C33))

Version: 1.5

Revision Date: 10.10.2024

Print Date: 11.10.2024

|                  |         |            |                         |                      |
|------------------|---------|------------|-------------------------|----------------------|
| titanium dioxide | Workers | Inhalation | Long-term local effects | 10 mg/m <sup>3</sup> |
|------------------|---------|------------|-------------------------|----------------------|

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

| Substance name                  | Environmental Compartment | Value       |
|---------------------------------|---------------------------|-------------|
| 2-Methoxy-1-methylethyl acetate | Fresh water               | 0.635 mg/l  |
|                                 | Marine water              | 0.0635 mg/l |
|                                 | Intermittent use/release  | 6.35 mg/l   |
|                                 | Sewage treatment plant    | 100 mg/l    |
|                                 | Fresh water sediment      | 3.29 mg/kg  |
|                                 | Marine sediment           | 0.329 mg/kg |
|                                 | Soil                      | 0.29 mg/kg  |
| titanium dioxide                | Fresh water               | 0.127 mg/l  |
|                                 | Marine water              | 1 mg/l      |
|                                 | Sewage treatment plant    | 100 mg/l    |
|                                 | Intermittent use/release  | 0.61 mg/l   |
|                                 | Fresh water sediment      | 1000 mg/kg  |
|                                 | Marine sediment           | 100 mg/kg   |
|                                 | Soil                      | 100 mg/kg   |
|                                 | Oral                      | 1667 mg/kg  |

## 8.2 Exposure controls

### Engineering measures

Handle only in a place equipped with local exhaust (or other appropriate exhaust).

### Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

#### Hand protection

Material : Protective gloves complying with EN 374.  
Break through time : > 60 min  
Protective index : Class 3

Material : Nitrile rubber  
Glove thickness : 0.4 mm

Material : butyl-rubber  
Glove thickness : 0.5 mm

Remarks : The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. The exact break through time can be obtained from the protective glove producer and this has to be observed.

Skin and body protection : Long sleeved clothing

Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.  
Recommended Filter type:  
A-P2  
The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorstift B.K.-2/3, 12 ml (mittelbronze (C33))

Version: 1.5

Revision Date: 10.10.2024

Print Date: 11.10.2024

contained breathing apparatus must be used.

Protective measures : Follow the skin protection plan.

### Environmental exposure controls

Water : Do not let product enter drains.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

|  |  |
|--|--|
| Physical state                                   | : liquid                               |
| Colour   | : According to product name            |
| Odour  | : characteristic                       |
| Melting point/ range                             | : No data available                    |
| Boiling point/boiling range                      | : 137 °C                               |
| Upper explosion limit / Upper flammability limit | : Upper flammability limit<br>7.5 %(V) |
| Lower explosion limit / Lower flammability limit | : Lower flammability limit<br>0.7 %(V) |
| Flash point                                      | : 30 °C                                |
| Auto-ignition temperature                        | : 315 °C                               |
| pH   | : No data available                    |
| Viscosity<br>Viscosity, kinematic                | : 26 mm <sup>2</sup> /s (40 °C)        |
| Solubility(ies)<br>Water solubility              | : immiscible to little miscible        |
| Partition coefficient: n-octanol/water           | : not determined                       |



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorstift B.K.-2/3, 12 ml (mittelbronze (C33))

Version: 1.5

Revision Date: 10.10.2024

Print Date: 11.10.2024

---

Vapour pressure : 5 hPa (20 °C)

Density : 0.96 g/cm<sup>3</sup> (20 °C)

Relative vapour density : not determined

### 9.2 Other information

Explosives : Vapours may form explosive mixture with air.

Flammability (liquids) : Combustible liquids

Self-ignition : not auto-flammable

Substances and mixtures,  
which in contact with water,  
emit flammable gases : No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

### 10.4 Conditions to avoid

Conditions to avoid : Product is stable under appropriate usage.

### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

### 10.6 Hazardous decomposition products

Hazardous decomposition  
products : Under fire conditions:  
Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorstift B.K.-2/3, 12 ml (mittelbronze (C33))

Version: 1.5

Revision Date: 10.10.2024

Print Date: 11.10.2024

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Not classified due to lack of data.

##### Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

##### Components:

##### **2-Methoxy-1-methylethyl acetate:**

Acute oral toxicity : LD50 (Rat): > 8,532 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 23.8 mg/l  
Exposure time: 6 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

##### **n-Butyl acetate:**

Acute oral toxicity : LD50 (Rat): 13,100 mg/kg

Acute inhalation toxicity : LC50 (Rat): 21 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 14,100 mg/kg

##### **titanium dioxide:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 425

Acute inhalation toxicity : LC50 (Rat): > 6.8 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

##### **Skin corrosion/irritation**

Not classified due to lack of data.

##### Product:

Remarks : No skin irritation

##### **Serious eye damage/eye irritation**

Not classified due to lack of data.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorstift B.K.-2/3, 12 ml (mittelbronze (C33))

Version: 1.5

Revision Date: 10.10.2024

Print Date: 11.10.2024

### Product:

Remarks : No eye irritation

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified due to lack of data.

#### Respiratory sensitisation

Not classified due to lack of data.

#### Germ cell mutagenicity

Not classified due to lack of data.

### Components:

#### 2-Methoxy-1-methylethyl acetate:

Genotoxicity in vitro : Remarks: In vitro tests did not show mutagenic effects

### Carcinogenicity

Based on available data, the classification criteria are not met.

### Product:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

### Reproductive toxicity

Not classified due to lack of data.

#### STOT - single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

#### STOT - repeated exposure

Not classified due to lack of data.

### Repeated dose toxicity

### Components:

#### titanium dioxide:

Species : Rat  
NOAEL : mg/kg bw/d, 3500  
Application Route : Oral  
Exposure time : 90 d

### Aspiration toxicity

Not classified due to lack of data.

## 11.2 Information on other hazards

### Endocrine disrupting properties

### Product:

Assessment : This substance/mixture does not contain components considered to have endocrine disrupting properties for human health

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorstift B.K.-2/3, 12 ml (mittelbronze (C33))

Version: 1.5

Revision Date: 10.10.2024

Print Date: 11.10.2024

according to UK REACH Article 57(f),

### Further information

#### Product:

Remarks : According to many years of experience, there are no known harmful effects when handled properly.  
Description of possible hazardous to health effects is based on experience and/or toxicological characteristics of several components.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### **2-Methoxy-1-methylethyl acetate:**

Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 500 mg/l  
Exposure time: 48 h  
Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC20 (activated sludge): > 1,000 mg/l  
Exposure time: 0.5 h  
Method: OECD Test Guideline 209

##### **n-Butyl acetate:**

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 62 mg/l  
Exposure time: 96 h  
  
LC50 (Lepomis macrochirus (Bluegill sunfish)): 100 mg/l  
Exposure time: 96 h

LC50 (Pimephales promelas (fathead minnow)): 18 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 73 mg/l  
Exposure time: 24 h

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 674.7 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : EC50 (Pseudomonas putida): 115 mg/l  
Exposure time: 16 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorstift B.K.-2/3, 12 ml (mittelbronze (C33))

Version: 1.5

Revision Date: 10.10.2024

Print Date: 11.10.2024

### titanium dioxide:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 203
- LC50 (Pimephales promelas (Fathead minnow)): > 1,000 mg/l  
Exposure time: 96 h  
Test Type: static test
- LC50 (Cyprinodon variegatus (sheepshead minnow)): > 10,000 mg/l  
Exposure time: 96 h  
Test Type: semi-static test  
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 16 mg/l  
Exposure time: 72 h  
Test Type: static test
- EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l  
Exposure time: 72 h  
Method: ISO 10253

## 12.2 Persistence and degradability

### Product:

- Biodegradability : Remarks: No data available

## 12.3 Bioaccumulative potential

### Product:

- Bioaccumulation : Remarks: No data available

## 12.4 Mobility in soil

### Product:

- Mobility : Remarks: No data available

### Components:

#### titanium dioxide:

- Distribution among environmental compartments : Medium: Soil  
Remarks: immobile

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorstift B.K.-2/3, 12 ml (mittelbronze (C33))

Version: 1.5

Revision Date: 10.10.2024

Print Date: 11.10.2024

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

### 12.7 Other adverse effects

**Product:**

Additional ecological information : Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Contaminated packaging : Dispose of in accordance with local regulations.

Waste Code : Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

---

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADR : UN 1263

RID : UN 1263

IMDG : UN 1263

IATA : UN 1263

### 14.2 UN proper shipping name

ADR : PAINT

RID : PAINT

IMDG : PAINT

IATA : Paint

### 14.3 Transport hazard class(es)

|     | Class | Subsidiary risks |
|-----|-------|------------------|
| ADR | : 3   |                  |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorstift B.K.-2/3, 12 ml (mittelbronze (C33))

Version: 1.5

Revision Date: 10.10.2024

Print Date: 11.10.2024

**RID** : 3  
**IMDG** : 3  
**IATA** : 3

### 14.4 Packing group

#### ADR

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)

#### RID

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

#### IMDG

Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Remarks : "IMDG-Code segregation group not applicable".

#### IATA (Cargo)

Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

#### IATA\_P (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

### 14.5 Environmental hazards

#### ADR

Environmentally hazardous : yes

#### RID

Environmentally hazardous : yes

#### IMDG

Marine pollutant : yes

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorstift B.K.-2/3, 12 ml (mittelbronze (C33))

Version: 1.5

Revision Date: 10.10.2024

Print Date: 11.10.2024

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

|   |   |   |
|---|---|---|
| UK REACH List of restrictions (Annex 17)  | : | Conditions of restriction for the following entries should be considered:<br>Number on list 3 |
| UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation                             | : | Not applicable  |
| The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) | : | Not applicable  |
| Regulation (EC) on substances that deplete the ozone layer  | : | Not applicable  |
| UK REACH List of substances subject to authorisation (Annex XIV)  | : | Not applicable  |
| GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation                           | : | Not applicable  |

#### Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

---

## SECTION 16: Other information

### Full text of H-Statements

|      |   |  |
|------|---|--|
| H226 | : | Flammable liquid and vapour.                             |
| H304 | : | May be fatal if swallowed and enters airways.            |
| H312 | : | Harmful in contact with skin.                            |
| H315 | : | Causes skin irritation.                                  |
| H319 | : | Causes serious eye irritation.                           |
| H332 | : | Harmful if inhaled.                                      |
| H335 | : | May cause respiratory irritation.                        |
| H336 | : | May cause drowsiness or dizziness.                       |
| H351 | : | Suspected of causing cancer if inhaled.                  |
| H373 | : | May cause damage to organs through prolonged or repeated |



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorstift B.K.-2/3, 12 ml (mittelbronze (C33))



A brand of BASF – we create chemistry

Version: 1.5

Revision Date: 10.10.2024

Print Date: 11.10.2024

- exposure.
- H411 : Toxic to aquatic life with long lasting effects.  
H412 : Harmful to aquatic life with long lasting effects.  
EUH066 : Repeated exposure may cause skin dryness or cracking.

### Full text of other abbreviations

- Acute Tox. : Acute toxicity  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Carc. : Carcinogenicity  
Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids  
Skin Irrit. : Skin irritation  
STOT RE : Specific target organ toxicity - repeated exposure  
STOT SE : Specific target organ toxicity - single exposure  
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits  
GB EH40 BAT : UK. Biological monitoring guidance values  
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)  
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

- Other information : The information provided is based on our current knowledge and experience and apply to the product as delivered. Re-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorstift B.K.-2/3, 12 ml (mittelbronze (C33))



A brand of BASF – we create chemistry

Version: 1.5

Revision Date: 10.10.2024

Print Date: 11.10.2024

garding the product properties, these are not guaranteed. The delivery of this safety datasheet does not free the recipient of the product from his own responsibility to follow the relevant rules and regulations concerning this product.

The product is classified and labelled in accordance with EC directives or respective national laws.

Regional or national implementations of GHS may not implement all hazard classes and categories.

Guideline on the Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment (RoHS) :  
no component is listed

No PFAS are consciously added to the product concerning the restriction proposal for inclusion to REACH (Annex XVII).

### Classification of the mixture:

|                   |      |
|-------------------|------|
| Flam. Liq. 3      | H226 |
| STOT SE 3         | H336 |
| STOT SE 3         | H335 |
| Aquatic Chronic 2 | H411 |

### Classification procedure:

|                                     |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |

GB / EN