

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorspray E-6 Natur (EV1), 150 ml (farblos (C0))

Version: 2.7

Revision Date: 12.03.2024

Print Date: 13.03.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Colorspray E-6 Natur (EV1), 150 ml (farblos (C0))

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Paint-aerosol  
stance/Mixture

#### 1.3 Details of the supplier of the safety data sheet

Company : hebro chemie- ZN der Rockwood Specialties Group  
GmbH  
Rostocker Str. 40  
41199 Mönchengladbach

Contact person : Zentrale hebro chemie  
Telephone : +49 (0) 2166 6009-0  
Telefax : +49 (0) 2166 6009-99

Contact person product safety : Abteilung Produktsicherheit  
Telephone : +49(0)2166 6009-311  
E-mail address : msds.de@hebro-chemie.de

#### 1.4 Emergency telephone number

: Giftinformationszentrum Erfurt:  
+49 (0) 361 730 730

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.  
H229: Pressurised container: May burst if heated.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single ex- H336: May cause drowsiness or dizziness.  
posure, Category 3, Central nervous  
system

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorspray E-6 Natur (EV1), 150 ml (farblos (C0))

Version: 2.7

Revision Date: 12.03.2024

Print Date: 13.03.2024

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing mist.  
P280 Wear eye protection/ face protection.

### Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

### Hazardous components which must be listed on the label:

Acetone  
n-Butyl acetate

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Mixture

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Substances with a workplace exposure limit :			
dimethyl ether	115-10-6 204-065-8 603-019-00-8 01-2119472128-37	Flam. Gas 1; H220 Press. Gas Liquefied gas; H280	>= 10 - < 25
Butane	106-97-8	Flam. Gas 1; H220	>= 2.5 - < 10

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorspray E-6 Natur (EV1), 150 ml (farblos (C0))



A brand of BASF – we create chemistry

Version: 2.7

Revision Date: 12.03.2024

Print Date: 13.03.2024

	203-448-7 601-004-00-0 01-2119474691-32	Press. Gas	
2-Methoxy-1-methylethyl acetate	108-65-6 203-603-9 01-2119475791-29	Flam. Liq. 3; H226	>= 2.5 - < 10
Ethanol	64-17-5 200-578-6 01-2119457610-43	Flam. Liq. 2; H225	>= 1 - < 2.5
Acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 25 - < 50
n-Butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Aquatic Chronic 3; H412 EUH066	>= 10 - < 20
Cellulose-nitrate	9004-70-0  603-037-01-3	Expl. 1.1; H201	>= 2.5 - < 10
Xylene	1330-20-7  01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315	>= 1 - < 2.5

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Call a physician if symptoms occur.
- If inhaled : Provide fresh air.  
Keep patient warm and at rest.  
If symptoms persist, call a physician.
- In case of skin contact : Take off immediately all contaminated clothing.  
Wash skin thoroughly with soap and water or use recognized skin cleanser.  
Do NOT use solvents or thinners.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,  
for at least 15 minutes.  
If eye irritation persists, consult a specialist.
- If swallowed : Call a physician immediately.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorspray E-6 Natur (EV1), 150 ml (farblos (C0))

Version: 2.7

Revision Date: 12.03.2024

Print Date: 13.03.2024

Keep at rest.  
Do NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Repeated exposure may cause skin dryness or cracking.

### 4.3 Indication of any immediate medical attention and special treatment needed

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Combustion may cause:  
Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Use water spray to cool unopened containers.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Provide sufficient air exchange and/or exhaust in work rooms.  
Remove all sources of ignition.  
Do not breathe vapour.  
Refer to protective measures listed in sections 7 and 8.

### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.  
Inform the relevant authorities if it enters sewers, aquatic environment or soil.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local /

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorspray E-6 Natur (EV1), 150 ml (farblos (C0))

Version: 2.7

Revision Date: 12.03.2024

Print Date: 13.03.2024

national regulations (see section 13).  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8., For disposal considerations see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Advice on safe handling : Do not breathe vapours or spray mist.  
When using do not eat, drink or smoke.  
For personal protection see section 8.  
Take precautionary measures against static discharges.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.  
Do not spray on a naked flame or any incandescent material.  
Keep away from sources of ignition - No smoking. Keep away from children.
- Advice on protection against fire and explosion : Vapours are heavier than air and may spread along floors.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Electrical installations / working materials must comply with the technological safety standards. Follow the water regulations.
- Further information on storage conditions : Keep only in the original container in a cool, well-ventilated place. Keep away from heat. Keep away from sources of ignition - No smoking.
- Advice on common storage : Incompatible with oxidizing agents.

### 7.3 Specific end use(s)

- Specific use(s) : Paint-aerosol

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Acetone	67-64-1	TWA	500 ppm 1,210 mg/m <sup>3</sup>	GB EH40
		STEL	1,500 ppm 3,620 mg/m <sup>3</sup>	GB EH40
dimethyl ether	115-10-6	TWA	400 ppm 766 mg/m <sup>3</sup>	GB EH40
		STEL	500 ppm	GB EH40

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorspray E-6 Natur (EV1), 150 ml (farblos (C0))

Version: 2.7

Revision Date: 12.03.2024

Print Date: 13.03.2024

n-Butyl acetate	123-86-4	TWA	958 mg/m <sup>3</sup> 150 ppm 724 mg/m <sup>3</sup>	GB EH40
		STEL	200 ppm 966 mg/m <sup>3</sup>	GB EH40
Butane	106-97-8	TWA	600 ppm 1,450 mg/m <sup>3</sup>	GB EH40
	Further information: Capable of causing cancer and/or heritable genetic damage., Carcinogenic only applies if butane contains more than 0.1% of buta-1,3-diene			
		STEL	750 ppm 1,810 mg/m <sup>3</sup>	GB EH40
	Further information: Capable of causing cancer and/or heritable genetic damage., Carcinogenic only applies if butane contains more than 0.1% of buta-1,3-diene			
		STEL	750 ppm 1,810 mg/m <sup>3</sup>	GB EH40
	Further information: Capable of causing cancer and/or heritable genetic damage., Carcinogenic only applies if butane contains more than 0.1% of buta-1,3-diene			
		TWA	600 ppm 1,450 mg/m <sup>3</sup>	GB EH40
	Further information: Capable of causing cancer and/or heritable genetic damage., Carcinogenic only applies if butane contains more than 0.1% of buta-1,3-diene			
		TWA	600 ppm 1,450 mg/m <sup>3</sup>	GB EH40
	Further information: Capable of causing cancer and/or heritable genetic damage.			
		STEL	750 ppm 1,810 mg/m <sup>3</sup>	GB EH40
	Further information: Capable of causing cancer and/or heritable genetic damage.			
2-Methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm 274 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 548 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
Xylene	1330-20-7	TWA	50 ppm 220 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 441 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorspray E-6 Natur (EV1), 150 ml (farblos (C0))

Version: 2.7

Revision Date: 12.03.2024

Print Date: 13.03.2024

Ethanol	64-17-5	TWA	1,000 ppm 1,920 mg/m <sup>3</sup>	GB EH40
---------	---------	-----	--------------------------------------	---------

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Xylene	1330-20-7	methyl hippuric acid: 650 Millimoles per mole creatinine (Urine)	After shift	GB EH40 BAT

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Acetone	Workers	Inhalation	Long-term systemic effects	1210 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	2420 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	1210 mg/m <sup>3</sup>
dimethyl ether	Workers	Skin contact	Long-term systemic effects	186 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	1894 mg/m <sup>3</sup>
n-Butyl acetate	Workers	Inhalation	Long-term systemic effects	480 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	480 mg/m <sup>3</sup>
2-Methoxy-1-methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	153.5 mg/kg bw/day
Xylene	Workers	Inhalation	Long-term systemic effects	77 mg/m <sup>3</sup>
Ethanol	Workers	Inhalation	Long-term systemic effects	950 mg/m <sup>3</sup>

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Acetone	Fresh water	10.6 mg/l
	Marine water	1.06 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	30.04 mg/kg
	Marine sediment	3.04 mg/kg
	Soil	29.5 mg/kg
2-Methoxy-1-methylethyl acetate	Fresh water	0.635 mg/l
	Marine water	0.0635 mg/l
	Intermittent use/release	6.35 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	3.29 mg/kg
	Marine sediment	0.329 mg/kg
	Soil	0.29 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorspray E-6 Natur (EV1), 150 ml (farblos (C0))

Version: 2.7

Revision Date: 12.03.2024

Print Date: 13.03.2024

### 8.2 Exposure controls

#### Engineering measures

Provide sufficient air exchange and/or exhaust in work rooms.

#### Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Hand protection

Material : Chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN 374.

Remarks : The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. The exact break through time can be obtained from the protective glove producer and this has to be observed.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Do not breathe gas/fumes/vapour/spray.  
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Protective measures : Handle in accordance with good industrial hygiene and safety practice.  
Follow the skin protection plan.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : aerosol

Colour : According to product name

Odour : characteristic

Melting point/freezing point : Not applicable

Boiling point/boiling range : No data available

Upper explosion limit / Upper flammability limit : Upper flammability limit  
18.6 %(V)

Lower explosion limit / Lower flammability limit : Lower flammability limit  
1.2 %(V)



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorspray E-6 Natur (EV1), 150 ml (farblos (C0))

Version: 2.7

Revision Date: 12.03.2024

Print Date: 13.03.2024

---

Flash point	:	No data available
Auto-ignition temperature	:	235 °C
pH	:	No data available
Viscosity Viscosity, kinematic	:	Not applicable
Solubility(ies) Water solubility	:	immiscible to little miscible
Partition coefficient: n- octanol/water	:	Not applicable
Vapour pressure	:	8,300 hPa (20 °C)
Density	:	0.78 g/cm <sup>3</sup> (20 °C)
Relative vapour density	:	not determined

### 9.2 Other information

Explosives	:	Vapours may form explosive mixture with air.
Self-ignition	:	not auto-flammable
Substances and mixtures, which in contact with water, emit flammable gases	:	Vapours may form explosive mixture with air.
Metal corrosion rate	:	Not applicable

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

The product is chemically stable.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorspray E-6 Natur (EV1), 150 ml (farblos (C0))

Version: 2.7

Revision Date: 12.03.2024

Print Date: 13.03.2024

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

### 10.4 Conditions to avoid

Conditions to avoid : No decomposition if used as directed.

### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

### 10.6 Hazardous decomposition products

In case of fire hazardous decomposition products may be produced such as:

Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide  
Nitrogen oxides (NO<sub>x</sub>)  
Smoke

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified due to lack of data.

#### Product:

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

#### Components:

##### **2-Methoxy-1-methylethyl acetate:**

Acute oral toxicity : LD50 (Rat): > 8,532 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 23.8 mg/l  
Exposure time: 6 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

##### **Ethanol:**

Acute oral toxicity : LD50 (Rat): 10,470 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 124.7 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorspray E-6 Natur (EV1), 150 ml (farblos (C0))

Version: 2.7

Revision Date: 12.03.2024

Print Date: 13.03.2024

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Method: OECD Test Guideline 402

### **Acetone:**

Acute oral toxicity : LD50 (Rat): 5,800 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): ca. 76 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 158,000 mg/kg

### **n-Butyl acetate:**

Acute oral toxicity : LD50 (Rat): 13,100 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 14,100 mg/kg

### **Skin corrosion/irritation**

Repeated exposure may cause skin dryness or cracking.

#### **Product:**

Remarks : Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin.  
May cause eye and skin irritation.

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

#### **Product:**

Remarks : Causes serious eye irritation.

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified due to lack of data.

#### **Respiratory sensitisation**

Not classified due to lack of data.

#### **Product:**

Remarks : This information is not available.

### **Germ cell mutagenicity**

Not classified due to lack of data.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorspray E-6 Natur (EV1), 150 ml (farblos (C0))

Version: 2.7

Revision Date: 12.03.2024

Print Date: 13.03.2024

### Components:

#### **2-Methoxy-1-methylethyl acetate:**

Genotoxicity in vitro : Remarks: In vitro tests did not show mutagenic effects

#### **Acetone:**

Genotoxicity in vitro : Test Type: Ames test  
Method: OECD Test Guideline 471  
Result: negative

Test Type: Ames test  
Method: OECD Test Guideline 476  
Result: negative

Genotoxicity in vivo : Test Type: in vivo assay  
Species: Mouse  
Application Route: Oral  
Result: negative

### **Carcinogenicity**

Based on available data, the classification criteria are not met.

### Product:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

### **Reproductive toxicity**

Not classified due to lack of data.

#### **STOT - single exposure**

May cause drowsiness or dizziness.

#### **STOT - repeated exposure**

Not classified due to lack of data.

### **Aspiration toxicity**

Not classified due to lack of data.

## 11.2 Information on other hazards

### **Further information**

### Product:

Remarks : Health injuries are not known or expected under normal use.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

### Components:

#### **2-Methoxy-1-methylethyl acetate:**

Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): > 100 mg/l  
Exposure time: 96 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorspray E-6 Natur (EV1), 150 ml (farblos (C0))

Version: 2.7

Revision Date: 12.03.2024

Print Date: 13.03.2024

Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 500 mg/l  
Exposure time: 48 h  
Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC20 (activated sludge): > 1,000 mg/l  
Exposure time: 0.5 h  
Method: OECD Test Guideline 209

### Ethanol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 13,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): 12,340 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Algae): 275 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

### Acetone:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5,540 mg/l  
Exposure time: 96 h  
Test Type: static test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 8,800 mg/l  
Exposure time: 48 h  
Test Type: static test

NOEC (Daphnia magna (Water flea)): 2,212 mg/l  
Exposure time: 28 d  
Test Type: flow-through test

Toxicity to algae/aquatic plants : NOEC (Algae): 430 mg/l  
Exposure time: 96 h  
Test Type: static test

NOEC (Microcystis aeruginosa (blue-green algae)): 530 mg/l  
Exposure time: 8 d  
Test Type: static test

Toxicity to microorganisms : (activated sludge):  
Exposure time: 30 min  
Test Type: Respiration inhibition

### n-Butyl acetate:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 62 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorspray E-6 Natur (EV1), 150 ml (farblos (C0))

Version: 2.7

Revision Date: 12.03.2024

Print Date: 13.03.2024

Exposure time: 96 h

LC50 (Lepomis macrochirus (Bluegill sunfish)): 100 mg/l  
Exposure time: 96 h

LC50 (Pimephales promelas (fathead minnow)): 18 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 73 mg/l  
aquatic invertebrates : Exposure time: 24 h

Toxicity to algae/aquatic : EC50 (Desmodesmus subspicatus (green algae)): 674.7 mg/l  
plants : Exposure time: 72 h

Toxicity to microorganisms : EC50 (Pseudomonas putida): 115 mg/l  
Exposure time: 16 h

### 12.2 Persistence and degradability

#### Product:

Biodegradability : Remarks: No data available

### 12.3 Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: No data available

### 12.4 Mobility in soil

#### Product:

Mobility : Remarks: No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

No data available

### 12.7 Other adverse effects

#### Product:

Additional ecological infor- : Do not flush into surface water or sanitary sewer system.  
mation

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorspray E-6 Natur (EV1), 150 ml (farblos (C0))

Version: 2.7

Revision Date: 12.03.2024

Print Date: 13.03.2024

- Product : Dispose of in accordance with local regulations.  
Do not let product enter drains.  
Do not dispose of with domestic refuse.
- Contaminated packaging : Dispose of in accordance with local regulations.
- Waste Code : Waste codes should be assigned by the user, preferably in  
discussion with the waste disposal authorities.

### SECTION 14: Transport information

#### 14.1 UN number or ID number

- ADR : UN 1950  
RID : UN 1950  
IMDG : UN 1950  
IATA : UN 1950

#### 14.2 UN proper shipping name

- ADR : AEROSOLS  
RID : AEROSOLS  
IMDG : AEROSOLS  
IATA : Aerosols, flammable

#### 14.3 Transport hazard class(es)

- |      | Class | Subsidiary risks |
|------|-------|------------------|
| ADR  | : 2   | 2.1              |
| RID  | : 2   | 2.1              |
| IMDG | : 2.1 |                  |
| IATA | : 2.1 |                  |

#### 14.4 Packing group

- ADR**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1  
Tunnel restriction code : (D)
- RID**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Hazard Identification Number : 23  
Labels : 2.1
- IMDG**  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U  
Remarks : "IMDG-Code segregation group not applicable", Protected

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorspray E-6 Natur (EV1), 150 ml (farblos (C0))

Version: 2.7

Revision Date: 12.03.2024

Print Date: 13.03.2024

from sources of heat., For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS or WASTE GAS CARTRIDGES: Category C, Clear of living quarters., For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

### IATA (Cargo)

Packing instruction (cargo aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

### IATA\_P (Passenger)

Packing instruction (passenger aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

## 14.5 Environmental hazards

### ADR

Environmentally hazardous : no

### RID

Environmentally hazardous : no

### IMDG

Marine pollutant : no

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained) : Not applicable



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorspray E-6 Natur (EV1), 150 ml (farblos (C0))



A brand of BASF – we create chemistry

Version: 2.7

Revision Date: 12.03.2024

Print Date: 13.03.2024

Regulation (EU) 2019/1021 as amended for Great Britain)

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

## SECTION 16: Other information

### Full text of H-Statements

H201	: Explosive; mass explosion hazard.
H220	: Extremely flammable gas.
H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H280	: Contains gas under pressure; may explode if heated.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H336	: May cause drowsiness or dizziness.
H412	: Harmful to aquatic life with long lasting effects.
EUH066	: Repeated exposure may cause skin dryness or cracking.

### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Expl.	: Explosives
Eye Irrit.	: Eye irritation
Flam. Gas	: Flammable gases
Flam. Liq.	: Flammable liquids
Press. Gas	: Gases under pressure
Skin Irrit.	: Skin irritation
STOT SE	: Specific target organ toxicity - single exposure
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	: UK. Biological monitoring guidance values
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization;

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Colorspray E-6 Natur (EV1), 150 ml (farblos (C0))



Version: 2.7

Revision Date: 12.03.2024

Print Date: 13.03.2024

KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Other information : The information provided is based on our current knowledge and experience and apply to the product as delivered. Regarding the product properties, these are not guaranteed. The delivery of this safety datasheet does not free the recipient of the product from his own responsibility to follow the relevant rules and regulations concerning this product.  
This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

### Classification of the mixture:

Aerosol 1	H222, H229
Eye Irrit. 2	H319
STOT SE 3	H336

### Classification procedure:

Calculation method
Calculation method
Calculation method

GB / EN