

Version: 2.0

Revision Date: 15.08.2022

Print Date: 16.08.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Colorspray B.K.-2/3, 150 ml (mittelbronze (C33))

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Paint-aerosol

1.3 Details of the supplier of the safety data sheet

Company : hebro chemie- ZN der Rockwood Specialties Group
GmbH
Rostocker Str. 40
41199 Mönchengladbach

Contact person : Zentrale hebro chemie
Telephone : +49 (0) 2166 6009-0
Telefax : +49 (0) 2166 6009-99

Contact person product safety : Abteilung Produktsicherheit
Telephone : +49(0)2166 6009-311
E-mail address : msds.de@hebro-chemie.de

1.4 Emergency telephone number

: Giftinformationszentrum Erfurt:
+49 (0) 361 730 730

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.
H229: Pressurised container: May burst if heated.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single ex-
posure, Category 3, Central nervous
system H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Colorspray B.K.-2/3, 150 ml (mittelbronze (C33))



A brand of BASF – we create chemistry

Version: 2.0

Revision Date: 15.08.2022

Print Date: 16.08.2022

Signal word	:	Danger
Hazard statements	:	H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.
Supplemental Hazard Statements	:	EUH066 Repeated exposure may cause skin dryness or cracking.
Precautionary statements	:	Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. Response: P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTER/ doctor if you feel unwell. Storage: P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Acetone

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

The information required is contained in this Material Safety Data Sheet.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Mixture

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (% w/w)
Acetone	67-64-1 200-662-2 01-2119471330-49	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 25 - < 50
Propane	74-98-6 200-827-9 01-2119486944-21	Flam. Gas 1; H220 Press. Gas Liquefied gas; H280 Note U (Table 3)	>= 10 - < 25

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Colorspray B.K.-2/3, 150 ml (mittelbronze (C33))



A brand of BASF – we create chemistry

Version: 2.0

Revision Date: 15.08.2022

Print Date: 16.08.2022

Isobutane	75-28-5 200-857-2 01-2119485395-27	Flam. Gas 1; H220 Press. Gas Liquefied gas; H280 Note U (Table 3) Note C	>= 2.5 - < 10
Ethanol	64-17-5 200-578-6 01-2119457610-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>= 1 - < 2.5
Substances with a workplace exposure limit :			
dimethyl ether	115-10-6 204-065-8 01-2119472128-37	Flam. Gas 1; H220 Press. Gas Liquefied gas; H280 Note U (Table 3)	>= 10 - < 25
n-Butyl acetate	123-86-4 204-658-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336	>= 10 - < 20
Butane	106-97-8 203-448-7 01-2119474691-32	Flam. Gas 1; H220 Press. Gas Liquefied gas; H280	>= 2.5 - < 10
2-Methoxy-1-methylethyl acetate	108-65-6 203-603-9 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336	>= 2.5 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Call a physician if symptoms occur.
- If inhaled : Provide fresh air.
Keep patient warm and at rest.
If symptoms persist, call a physician.
- In case of skin contact : Take off immediately all contaminated clothing.
Wash skin thoroughly with soap and water or use recognized skin cleanser.
Do NOT use solvents or thinners.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,
for at least 15 minutes.
If eye irritation persists, consult a specialist.
- If swallowed : Call a physician immediately.
Keep at rest.
Do NOT induce vomiting.

Version: 2.0

Revision Date: 15.08.2022

Print Date: 16.08.2022

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No information available.

Risks : No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Combustion may cause:
Carbon dioxide (CO₂)
Carbon monoxide

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Use water spray to cool unopened containers.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Provide sufficient air exchange and/or exhaust in work rooms.
Remove all sources of ignition.
Do not breathe vapour.
Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.
Inform the relevant authorities if it enters sewers, aquatic environment or soil.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.

Version: 2.0

Revision Date: 15.08.2022

Print Date: 16.08.2022

6.4 Reference to other sections

See chapter
8
and
13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Do not breathe vapours or spray mist.
When using do not eat, drink or smoke.
For personal protection see section 8.
Take precautionary measures against static discharges.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material.
Keep away from sources of ignition - No smoking. Keep away from children.
- Advice on protection against fire and explosion : Vapours are heavier than air and may spread along floors.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Electrical installations / working materials must comply with the technological safety standards. Follow the water regulations.
- Further information on storage conditions : Keep only in the original container in a cool, well-ventilated place. Keep away from heat. Keep away from sources of ignition - No smoking.
- Advice on common storage : Incompatible with oxidizing agents.

7.3 Specific end use(s)

- Specific use(s) : Paint-aerosol

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Acetone	67-64-1	TWA	500 ppm 1,210 mg/m ³	2000/39/EC
Further information	Indicative			
		TWA	500 ppm 1,210 mg/m ³	GB EH40
		STEL	1,500 ppm 3,620 mg/m ³	GB EH40

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Colorspray B.K.-2/3, 150 ml (mittelbronze (C33))

Version: 2.0

Revision Date: 15.08.2022

Print Date: 16.08.2022

dimethyl ether	115-10-6	TWA	1,000 ppm 1,920 mg/m ³	2000/39/EC
Further information	Indicative			
		TWA	400 ppm 766 mg/m ³	GB EH40
		STEL	500 ppm 958 mg/m ³	GB EH40
n-Butyl acetate	123-86-4	TWA	150 ppm 724 mg/m ³	GB EH40
		STEL	200 ppm 966 mg/m ³	GB EH40
		STEL	150 ppm 723 mg/m ³	2019/1831/E U
Further information	Indicative			
		TWA	50 ppm 241 mg/m ³	2019/1831/E U
Further information	Indicative			
Butane	106-97-8	TWA	600 ppm 1,450 mg/m ³	GB EH40
Further information	Capable of causing cancer and/or heritable genetic damage., Carcinogenic only applies if butane contains more than 0.1% of buta-1,3-diene			
		STEL	750 ppm 1,810 mg/m ³	GB EH40
Further information	Capable of causing cancer and/or heritable genetic damage., Carcinogenic only applies if butane contains more than 0.1% of buta-1,3-diene			
		STEL	750 ppm 1,810 mg/m ³	GB EH40
Further information	Capable of causing cancer and/or heritable genetic damage., Carcinogenic only applies if butane contains more than 0.1% of buta-1,3-diene			
		TWA	600 ppm 1,450 mg/m ³	GB EH40
Further information	Capable of causing cancer and/or heritable genetic damage., Carcinogenic only applies if butane contains more than 0.1% of buta-1,3-diene			
2-Methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm 275 mg/m ³	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 550 mg/m ³	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 274 mg/m ³	GB EH40
Further information	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 548 mg/m ³	GB EH40
Further information	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
Ethanol	64-17-5	TWA	1,000 ppm 1,920 mg/m ³	GB EH40
Further information	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Colorspray B.K.-2/3, 150 ml (mittelbronze (C33))



A brand of BASF – we create chemistry

Version: 2.0

Revision Date: 15.08.2022

Print Date: 16.08.2022

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Acetone	Workers	Inhalation	Long-term systemic effects	1210 mg/m ³
	Workers	Inhalation	Long-term local effects	2420 mg/m ³
	Workers	Inhalation	Acute systemic effects	1210 mg/m ³
	Workers	Skin contact	Long-term systemic effects	186 mg/kg bw/day
Ethanol	Workers	Inhalation	Long-term systemic effects	950 mg/m ³
dimethyl ether	Workers	Inhalation	Long-term systemic effects	1894 mg/m ³
n-Butyl acetate	Workers	Inhalation	Long-term systemic effects	480 mg/m ³
	Workers	Inhalation	Long-term local effects	480 mg/m ³
2-Methoxy-1-methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275 mg/m ³
	Workers	Skin contact	Long-term systemic effects	153.5 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Acetone	Fresh water	10.6 mg/l
	Marine water	1.06 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	30.04 mg/kg
	Marine sediment	3.04 mg/kg
	Soil	29.5 mg/kg
2-Methoxy-1-methylethyl acetate	Fresh water	0.635 mg/l
	Marine water	0.0635 mg/l
	Intermittent use/release	6.35 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	3.29 mg/kg
	Marine sediment	0.329 mg/kg
	Soil	0.29 mg/kg

8.2 Exposure controls

Engineering measures

Provide sufficient air exchange and/or exhaust in work rooms.

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Hand protection

Material : Chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN 374.

Remarks : The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. The exact break through time can be obtained from the protective glove producer and this

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Colorspray B.K.-2/3, 150 ml (mittelbronze (C33))

Version: 2.0

Revision Date: 15.08.2022

Print Date: 16.08.2022

has to be observed.

- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : Do not breathe gas/fumes/vapour/spray.
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
- Protective measures : Handle in accordance with good industrial hygiene and safety practice.
Follow the skin protection plan.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance : aerosol
- Colour : According to product name
- Odour : characteristic
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : No data available
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit : Upper flammability limit
18.6 %(V)
- Lower explosion limit : Lower flammability limit
1.2 %(V)
- Vapour pressure : 8,300 hPa (20 °C)
- Relative vapour density : No data available
- Relative density : No data available
- Density : 0.78 g/cm³ (20 °C)
- Solubility(ies)
Water solubility : immiscible to little miscible
- Solubility in other solvents : No data available
- Partition coefficient: n- : No data available

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Colorspray B.K.-2/3, 150 ml (mittelbronze (C33))

Version: 2.0

Revision Date: 15.08.2022

Print Date: 16.08.2022

octanol/water

Auto-ignition temperature	:	235 °C
Decomposition temperature	:	No data available
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Flow time	:	No data available
Explosive properties	:	Vapours may form explosive mixture with air.
Oxidizing properties	:	No data available

9.2 Other information

Other physico-chemical properties: This information is not available/not determined.

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : No decomposition if used as directed.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

In case of fire hazardous decomposition products may be produced such as:

Carbon dioxide (CO₂)
Carbon monoxide
Nitrogen oxides (NO_x)
Smoke

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Colorspray B.K.-2/3, 150 ml (mittelbronze (C33))

Version: 2.0

Revision Date: 15.08.2022

Print Date: 16.08.2022

Acute toxicity

Components:

Acetone:

Acute oral toxicity : LD50 (Rat): 5,800 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): ca. 76 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 158,000 mg/kg

Ethanol:

Acute oral toxicity : LD50 (Rat): 10,470 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 124.7 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Method: OECD Test Guideline 402

n-Butyl acetate:

Acute oral toxicity : LD50 (Rat): 13,100 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 14,100 mg/kg

2-Methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 (Rat): > 8,532 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 23.8 mg/l
Exposure time: 6 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Product:

Remarks: Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin.

May cause eye and skin irritation.

Version: 2.0

Revision Date: 15.08.2022

Print Date: 16.08.2022

Serious eye damage/eye irritation

Product:

Remarks: Causes serious eye irritation.

Respiratory or skin sensitisation

Product:

Remarks: This information is not available.

Germ cell mutagenicity

Product:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Components:

Acetone:

Genotoxicity in vitro : Test Type: Ames test
Method: OECD Test Guideline 471
Result: negative

: Test Type: Ames test
Method: OECD Test Guideline 476
Result: negative

Genotoxicity in vivo : Test Type: in vivo assay
Species: Mouse
Application Route: Oral
Result: negative

2-Methoxy-1-methylethyl acetate:

Genotoxicity in vitro : Remarks: In vitro tests did not show mutagenic effects

Carcinogenicity

Product:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

Reproductive toxicity

Product:

Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Based on available data, the classification criteria are not met.

Version: 2.0

Revision Date: 15.08.2022

Print Date: 16.08.2022

STOT - repeated exposure

Product:

Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Based on available data, the classification criteria are not met.

Further information

Product:

Remarks: Health injuries are not known or expected under normal use.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology studies for the product are not available.

Components:

Acetone:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5,540 mg/l
Exposure time: 96 h
Test Type: static test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 8,800 mg/l
Exposure time: 48 h
Test Type: static test

NOEC (Daphnia magna (Water flea)): 2,212 mg/l
Exposure time: 28 d
Test Type: flow-through test

Toxicity to algae : NOEC (Algae): 430 mg/l
Exposure time: 96 h
Test Type: static test

NOEC (Microcystis aeruginosa (blue-green algae)): 530 mg/l
Exposure time: 8 d
Test Type: static test

Toxicity to microorganisms : (activated sludge):
Exposure time: 30 min
Test Type: Respiration inhibition

Ethanol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 13,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): 12,340 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Colorspray B.K.-2/3, 150 ml (mittelbronze (C33))



A brand of BASF – we create chemistry

Version: 2.0

Revision Date: 15.08.2022

Print Date: 16.08.2022

Toxicity to algae : EC50 (Algae): 275 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

n-Butyl acetate:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 62 mg/l
Exposure time: 96 h

LC50 (Lepomis macrochirus (Bluegill sunfish)): 100 mg/l
Exposure time: 96 h

LC50 (Pimephales promelas (fathead minnow)): 18 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 73 mg/l
Exposure time: 24 h

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): 674.7 mg/l
Exposure time: 72 h

Toxicity to microorganisms : EC50 (Pseudomonas putida): 115 mg/l
Exposure time: 16 h

2-Methoxy-1-methylethyl acetate:

Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 500 mg/l
Exposure time: 48 h
Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC20 (activated sludge): > 1,000 mg/l
Exposure time: 0.5 h
Method: OECD Test Guideline 209

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Version: 2.0

Revision Date: 15.08.2022

Print Date: 16.08.2022

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.
Do not let product enter drains.
Do not dispose of with domestic refuse.

Contaminated packaging : Dispose of in accordance with local regulations.

Waste Code : 16 05 04 : gases in pressure containers (including halons) containing hazardous substances

SECTION 14: Transport information

14.1 UN number

ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS
IATA : Aerosols, flammable

14.3 Transport hazard class(es)

ADR : 2

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Colorspray B.K.-2/3, 150 ml (mittelbronze (C33))

Version: 2.0

Revision Date: 15.08.2022

Print Date: 16.08.2022

RID : 2
IMDG : 2.2
IATA : 2.1

14.4 Packing group

ADR

Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1
Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation
Classification Code : 5F
Hazard Identification Number : 23
Labels : 2.1

IMDG

Packing group : Not assigned by regulation
Labels : 2.2
EmS Code : F-D, S-U
Remarks : "IMDG-Code segregation group not applicable"., Protected from sources of heat., For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS or WASTE GAS CARTRIDGES: Category C, Clear of living quarters., For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

IATA (Cargo)

Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

14.5 Environmental hazards

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Colorspray B.K.-2/3, 150 ml (mittelbronze (C33))



A brand of BASF – we create chemistry

Version: 2.0

Revision Date: 15.08.2022

Print Date: 16.08.2022

14.6 Special precautions for user

Refer to protective measures listed in sections 7 and 8.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H220 : Extremely flammable gas.
H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.
H280 : Contains gas under pressure; may explode if heated.
H319 : Causes serious eye irritation.
H336 : May cause drowsiness or dizziness.

Full text of other abbreviations

Eye Irrit. : Eye irritation
Flam. Gas : Flammable gases
Flam. Liq. : Flammable liquids
Press. Gas : Gases under pressure
STOT SE : Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Stand-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Colorspray B.K.-2/3, 150 ml (mittelbronze (C33))



A brand of BASF – we create chemistry

Version: 2.0

Revision Date: 15.08.2022

Print Date: 16.08.2022

ardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information

: The information provided is based on our current knowledge and experience and apply to the product as delivered. Regarding the product properties, these are not guaranteed. The delivery of this safety datasheet does not free the recipient of the product from his own responsibility to follow the relevant rules and regulations concerning this product. This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

GB / EN