

Technical Information

Colorex 1008

Modern, newly developed, high-performance paint stripper

Colorex 1008 is a ready-to-use paint stripper for removing paint from a wide variety of paint systems on all metal surfaces.

Properties

- Effortlessly removes a wide variety of paint and powder coatings (incl. polyester lacquers) from all metal surfaces, especially aluminium.
- Easy to use and particularly economical due to its fast action.
- Amine-free and produces only low emissions.
- Suitable for use in immersion methods.

Technical specifications (typical values)

Colour	Smell	Flashpoint	Density at 20°C	pH value (1% solution)
Colourless	characteristic	>100°C	1.066 g/cm ³	10.6

Dosing

- It is applied by immersion at a temperature of 20°C to 60°C (55°C for aluminium and galvanised sheets).
- The times required for paint stripping depend on the paint type, paint density, paint age and tank temperature.
- The introduction of water into the paint stripping tank should be avoided, as otherwise metals such as aluminium, zinc as well as non-ferrous metals may be attacked.

Information

The maximum shelf life in the sealed original container is 12 months from the date of production.
Store the product frost-free at 5 – 40°C. Disposal of completely empty containers is possible via our Interseroh system.

The information provided in this data sheet is based on the properties and possible applications known to us. In general, however, no legal obligation can be derived from this data.
We reserve the right to make changes to the product if these are necessary due to legislation or the lack of supply of raw materials.